




# CoroThread® 266 wisselplaat voor draadsnijden

ACME 29° Aangeschuinde draadtop

STDNO  
TCTR

ANSI B1.5-1988  
2G



## Uitwendige rechtse draad

TPI	NT	Bestelcode	P		M		K		N		S		H		Afmetingen, mm					
			1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	CF	HA	HB	PDX	PDY	
16	16.0	1	266RG-16AC01F160E	*	*	*	*	*	*	*	*	*	*	*	☆	0.5	1.98	1.04	1.00	1.33
	14.0	1	266RG-16AC01F140E	*	*	*	*	*	*	*	*	*	*	*	☆	0.6	2.26	1.21	1.10	1.33
	12.0	1	266RG-16AC01F120E	*	*	*	*	*	*	*	*	*	*	*	☆	0.7	2.64	1.43	1.20	1.33
	10.0	1	266RG-16AC01F100E	*	*	*	*	*	*	*	*	*	*	*	☆	0.8	3.16	1.61	1.30	1.32
	8.0	1	266RG-16AC01F080E	*	*	*	*	*	*	*	*	*	*	*	☆	1.1	3.94	2.08	1.50	1.23
22	6.0	1	266RG-22AC01F060E	*	*	*	*	*	*	*	*	*	*	*	☆	1.5	5.25	2.84	1.90	1.38
	5.0	1	266RG-22AC01F050E	*	*	*	*	*	*	*	*	*	*	*	☆	1.8	6.29	3.47	2.10	1.38
	4.0	1	266RG-22AC01F040E	*	*	*	*	*	*	*	*	*	*	*	☆	2.3	7.87	4.41	2.40	0.79
27	3.0	1	266RG-27AC01F030E	*	*	*	*	*	*	*	*	*	*	*	☆	3.1	10.47	5.95	3.30	0.54

## Uitwendige linkse draad

TPI	NT	Bestelcode	P		M		K		N		S		H		Afmetingen, mm					
			1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	CF	HA	HB	PDX	PDY	
16	12.0	1	266LG-16AC01F120E	*	*	*	*	*	*	*	*	*	*	*	☆	0.7	2.64	1.43	1.20	1.33
	10.0	1	266LG-16AC01F100E	*	*	*	*	*	*	*	*	*	*	*	☆	0.8	3.16	1.61	1.30	1.33
	8.0	1	266LG-16AC01F080E	*	*	*	*	*	*	*	*	*	*	*	☆	1.1	3.94	2.08	1.50	1.23
22	6.0	1	266LG-22AC01F060E	*	*	*	*	*	*	*	*	*	*	*	☆	1.5	5.25	2.84	1.90	1.38
	5.0	1	266LG-22AC01F050E	*	*	*	*	*	*	*	*	*	*	*	☆	1.8	6.29	3.47	2.10	1.38
	4.0	1	266LG-22AC01F040E	*	*	*	*	*	*	*	*	*	*	*	☆	2.3	7.87	4.41	2.40	0.79

## Inwendige rechtse draad

TPI	NT	Bestelcode	P		M		K		N		S		H		Afmetingen, mm						
			1020	1125	1135	1020	1125	1135	1020	1125	1135	1020	1125	1135	1020	1125	1135	CF	HA	HB	PDX
16	16.0	1	266RL-16AC01F160E			*		*		*		*		*		☆	0.5	1.97	1.00	1.00	1.30
	14.0	1	266RL-16AC01F140E			*		*		*		*		*		☆	0.6	2.25	1.16	1.10	1.30
	12.0	1	266RL-16AC01F120E			*		*		*		*		*		☆	0.7	2.62	1.37	1.20	1.30
	10.0	1	266RL-16AC01F100E			*		*		*		*		*		☆	0.8	3.13	1.54	1.30	1.30
	8.0	1	266RL-16AC01F080E			*		*		*		*		*		☆	1.0	3.90	2.00	1.50	1.21
22	6.0	1	266RL-22AC01A060M	*	*	*	*	*	*	*	*	*	*	*	☆	1.4	5.19	2.76	1.90	1.01	
	6.0	1	266RL-22AC01F060E	*		*		*		*		*		*	☆	1.4	5.19	2.76	1.90	1.35	
	5.0	1	266RL-22AC01F050E	*		*		*		*		*		*	☆	1.7	6.22	3.37	2.10	0.96	
	4.0	1	266RL-22AC01F040E	*		*		*		*		*		*	☆	2.2	7.77	4.28	2.40	0.87	
27	3.0	1	266RL-27AC01F030E	*		*		*		*		*		*	☆	3.0	10.31	5.80	3.30	0.54	

## Inwendige linkse draad

TPI	NT	Bestelcode	P		M		K		N		S		H		Afmetingen, mm					
			1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	1020	1135	CF	HA	HB	PDX	PDY	
16	12.0	1	266LL-16AC01F120E	*	*	*	*	*	*	*	*	*	*	*	☆	0.7	2.62	1.37	1.20	1.30
	10.0	1	266LL-16AC01F100E	*	*	*	*	*	*	*	*	*	*	*	☆	0.8	3.13	1.54	1.30	1.30
	8.0	1	266LL-16AC01F080E	*	*	*	*	*	*	*	*	*	*	*	☆	1.0	3.90	2.00	1.50	1.21
22	6.0	1	266LL-22AC01F060E	*	*	*	*	*	*	*	*	*	*	*	☆	1.4	5.19	2.76	1.90	1.35
	5.0	1	266LL-22AC01F050E	*	*	*	*	*	*	*	*	*	*	*	☆	1.7	6.22	3.37	2.00	0.96
	4.0	1	266LL-22AC01F040E	*	*	*	*	*	*	*	*	*	*	*	☆	2.2	7.77	4.28	2.40	0.70


R = Rechts, L = Links



C30



C39



C73



C83



H36



H35



H26