



# CoroThread® 266 wisselplaat voor draadsnijden


NPT 60° (NPSC, NPTR, LINE PIPE) Volprofiel




STDNO



ANSI B.1.20.1-1983



ANSI B.1.20.1-1983



## Uitwendige rechtse draad

TPI	NT	Bestelcode	Afmetingen, mm												
			P	M	K	N	S	H							
			1125	1135	1125	1135	1125	1135	1125	1135	HA	HB	PDX	PDY	TG
16	27.0	1	★	☆	★	☆	★	☆	★	☆	0,76	0,05	0,80	1,03	0,03
	18.0	1	★	☆	★	☆	★	☆	★	☆	1,14	0,08	1,00	1,03	0,03
	14.0	1	★	☆	★	☆	★	☆	★	☆	1,46	0,09	1,20	1,03	0,03
	14.0	1	★	★	★	★	★	★	★	★	1,46	0,09	1,20	1,03	0,03
	14.0	1	★	★	★	★	★	★	★	★	1,46	0,09	1,20	1,03	0,03
	11.5	1	★	★	★	★	★	★	★	★	1,79	0,11	1,40	1,03	0,03
	11.5	1	★	★	★	★	★	★	★	★	1,79	0,11	1,40	1,03	0,03
	11.5	1	★	★	★	★	★	★	★	★	1,79	0,11	1,40	1,03	0,03
	8.0	1	★	★	★	★	★	★	★	★	2,57	0,14	1,60	1,03	0,03
	8.0	1	★	★	★	★	★	★	★	★	2,57	0,14	1,60	1,03	0,03

## Uitwendige rechtse draad - multipunt wisselplaat

TPI	NT	Bestelcode	Afmetingen, mm									
			P	M	K	N	S					
			1020	1020	1020	1020	1020	HA	HB	PDX	PDY	TG
22	11.5	2	★	★	★	★	★	1,79	0,11	3,40	1,67	0,03

## Uitwendige linkse draad

TPI	NT	Bestelcode	Afmetingen, mm									
			P	M	K	N	S	H				
			1125	1125	1125	1125	1125	HA	HB	PDX	PDY	TG
16	27.0	1	★	★	★	★	★	0,76	0,05	0,80	1,03	0,03
	18.0	1	★	★	★	★	★	1,14	0,08	1,00	1,03	0,03
	14.0	1	★	★	★	★	★	1,46	0,09	1,20	1,03	0,03
	11.5	1	★	★	★	★	★	1,79	0,11	1,40	1,03	0,03
	8.0	1	★	★	★	★	★	2,57	0,14	1,60	1,03	0,03


R = Rechts, L = Links



C30



C39



C73



C83



H36



H35



H26