

A

DRAADSNIJDEN



Wisselplaten

CoroThread® 266 wisselplaat voor draadsnijden

NPTF 60° Volprofiel

STDNO
TCTRANSI B1.20.3-1976
IT 2

B



C

Uitwendige rechtse draad

		P	M	K	N	S	H	Afmetingen, mm				
	TPI	NT	Bestelcode	1125	1125	1125	1125	HA	HB	PDX	PDY	TG
16	27.0	1	266RG-16NF01A270E	★	★	★	★	0.75	0.11	0.80	1.03	0.03
	18.0	1	266RG-16NF01A180E	★	★	★	★	1.14	0.13	1.00	1.03	0.03
	14.0	1	266RG-16NF01A140E	★	★	★	★	1.49	0.13	1.20	1.03	0.03
	11.5	1	266RG-16NF01A115E	★	★	★	★	1.81	0.17	1.40	1.03	0.03
	8.0	1	266RG-16NF01A080E	★	★	★	★	2.60	0.21	1.60	1.03	0.03

D

Inwendige rechtse draad


		P	M	K	N	S	H	Afmetingen, mm				
	TPI	NT	Bestelcode	1125	1125	1125	1125	HA	HB	PDX	PDY	TG
16	14.0	1	266RL-16NF01A140E	★	★	★	★	1.49	0.13	1.20	1.01	0.03
	11.5	1	266RL-16NF01A115E	★	★	★	★	1.81	0.17	1.40	1.01	0.03
	8.0	1	266RL-16NF01A080E	★	★	★	★	2.60	0.21	1.60	1.01	0.03

R = rechts

F

G


H



C30



C39



C73



C83



H36



H35



H26

C 20

SANDVIK
Coromant