

1

M	spoed P mm	l1 mm	d2 mm	vierkant a _{h12} mm	5613	
					standaard	HSS
DIN352						
33	1,5	100	25,0	20,0	F	
33	2	100	25,0	20,0	F	
33	3	125	25,0	20,0	F	
34	1	100	28,0	22,0	F	
34	1,5	100	28,0	22,0	F	
34	2	125	28,0	22,0	F	
35	1	100	28,0	22,0	F	
35	1,5	100	28,0	22,0	F	
35	2	125	28,0	22,0	F	
36	1	100	28,0	22,0	F	
36	1,5	100	28,0	22,0	F	
36	2	125	28,0	22,0	F	
36	3	125	28,0	22,0	F	
37	1,5	100	28,0	22,0	F	
38	1	100	28,0	22,0	F	
38	1,5	100	28,0	22,0	F	
38	2	125	28,0	22,0	F	
38	3	125	28,0	22,0	F	

S = magazijnartikel - F = fabriekslevering op 24/48h

M	spoed P mm	l1 mm	d2 mm	vierkant a _{h12} mm	5613	
					standaard	HSS
DIN352						
39	1,5	110	32,0	24,0	F	
39	2	125	32,0	24,0	F	
39	3	125	32,0	24,0	F	
40	1	110	32,0	24,0	F	
40	1,5	110	32,0	24,0	F	
40	2	125	32,0	24,0	F	
40	3	125	32,0	24,0	F	
42	1	110	32,0	24,0	F	
42	1,5	110	32,0	24,0	F	
42	2	125	32,0	24,0	F	
42	3	125	32,0	24,0	F	
44	1,5	110	36,0	29,0	F	
44	2	125	36,0	29,0	F	
45	1	110	36,0	29,0	F	
45	1,5	110	36,0	29,0	F	
45	2	125	36,0	29,0	F	
45	3	125	36,0	29,0	F	

S = magazijnartikel - F = fabriekslevering op 24/48h

GAZ (BSP) - handtappen

4573

Set handtappen (2 stuks), HSS
Staal < 850N/mm², gietijzer, koper, aluminium



G	P gangen/"	l1 mm	d2 mm	vierkant a _{h12} mm	4573	
					standaard	HSS
DIN5157						
1/8"	28	63	7,0	5,5	S	
1/4"	19	70	11,0	9,0	S	
3/8"	19	70	12,0	9,0	S	
1/2"	14	80	16,0	12,0	S	
5/8"	14	80	18,0	14,5	S	
3/4"	14	90	20,0	16,0	S	
7/8"	14	90	22,0	18,0	S	
1"	11	100	25,0	20,0	S	
1-1/8"	11	125	28,0	22,0	F	
1-1/4"	11	125	32,0	24,0	F	
1-3/8"	11	140	36,0	29,0	F	
1-1/2"	11	140	36,0	29,0	F	
1-5/8"	11	140	40,0	32,0	F	
1-3/4"	11	140	40,0	32,0	F	
2"	11	160	45,0	35,0	F	
2-1/4"	11	160	50,0	39,0	F	
2-1/2"	11	160	50,0	39,0	F	
2-3/4"	11	160	50,0	39,0	F	
3"	11	160	50,0	39,0	F	
3-1/2"	11	180	56,0	44,0	F	
4"	11	180	56,0	44,0	F	

S = magazijnartikel - F = fabriekslevering op 24/48h

