

EXTRA80-RV



APPLICATION

For corded and cordless drills with and without spindle stop up to a maximum torque of 100 Nm and up to 1500 watt.

TYPE

Impact-resistant quick-action drill chuck with radial locking and plastic or metal sleeve.
Optional with retaining ring for machines without spindle stop.
With through-hole for use of a locking screw.

CUSTOMER BENEFITS

- ☉ Easy clamping and locking with one manual operation for maximum user-friendliness
- ☉ Radial locking device to prevent release of the drill bit during clockwise and counterclockwise rotation
- ☉ Impact-resistant for universal use

TECHNICAL FEATURES

- With carbide inserts in the clamping jaws
- Equipped with collision protector by freely rotating protection disc



A01 EXTRA80-RV with radial locking, metal design



Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Max. mach. capacity watt	Through-hole
1328321	10	1-10	3/8"-24		metal	0,4	42,7	55	60,9	550	•
1328318	10	1-10	1/2"-20		metal	0,4	42,7	55	60,9	550	•
1328317	10	1-10	1/2"-20	•	metal	0,4	42,7	55	60,9	550	•
1328314	13	1,5-13	3/8"-24	•	metal	0,4	42,7	64,5	72,4	1500	•
1328311	13	1,5-13	1/2"-20		metal	0,4	42,7	64,5	72,4	1500	•
1328310	13	1,5-13	1/2"-20	•	metal	0,4	42,7	64,5	72,4	1500	•
1339960	13	1,5-13	9/16"-18		metal	0,4	42,7	64,5	72,4	1500	•

Note: locking screw is not included in scope of delivery

A01 EXTRA80-RV with radial locking, plastic design



Item no.	Size	Clamping capacity mm	Mount	Retaining ring	Design	Concentricity deviation max. mm	External Ø mm	Length opened mm	Length closed mm	Max. mach. capacity watt	Through-hole
1328323	10	1-10	3/8"-24		plastic	0,4	42,7	55	60,9	550	•
1328322	10	1-10	3/8"-24	•	plastic	0,4	42,7	55	60,9	550	•
1328320	10	1-10	1/2"-20		plastic	0,4	42,7	55	60,9	550	•
1328319	10	1-10	1/2"-20	•	plastic	0,4	42,7	55	60,9	550	•
1328316	13	1,5-13	3/8"-24		plastic	0,4	42,7	64,5	72,4	1300	•
1328315	13	1,5-13	3/8"-24	•	plastic	0,4	42,7	64,5	72,4	1300	•
1328313	13	1,5-13	1/2"-20		plastic	0,4	42,7	64,5	72,4	1300	•
1328312	13	1,5-13	1/2"-20	•	plastic	0,4	42,7	64,5	72,4	1300	•

Note: locking screw is not included in scope of delivery