


Hard part turning

WITH THE NEW GENERATION OF CBN GRADES

GENERAL TURNING
PARTING AND GROOVING
THREAD TURNING



Hard part turning

Turning of steel with a hardness of typically 55-65 HRC is defined as hard part turning and is a cost-efficient alternative to grinding. Hard part turning has been proven to reduce machining time and costs by 70% or more, and offers improved flexibility, better lead times and higher quality.

- Simpler production process, like normal turning
- Flexible machine utilization; use the same machine for external and internal machining
- Increased productivity and lower costs per part
- Complex component shapes machined in one set-up
- Environmentally friendly - no coolant, no grinding waste



Components

Hard part turning is a well-accepted method. Typical parts are transmission gears, pinions, valve seats, pistons, cylinder liners, input/output shaft, crown wheel and CV-joint (inner/outer race & cage).



Cutting tool materials

Cubic Boron Nitride grades (CBN) are the ultimate cutting tool material for hard part turning of case and induction hardened steels.




Key factors in hard part turning

Careful preparation of the component in the soft (unhardened) state will benefit the hard part turning process. Due to the relatively small depths of cut used in hard part turning, tight dimensional tolerances in soft machining are key to achieving a consistent process. This delivers longer tool life and high quality components. The use of features such as chamfers and radii on the component will optimise entry and exit paths for maximum tool life.


Points to remember when planning your soft machining conditions include:

- Avoid burrs
- Keep close dimensional tolerances
- Chamfer and make radii in the soft state
- Do not enter or leave cut abruptly
- Enter or leave by programming radius movement



Set-up

- Good machine stability, clamping and alignment of workpiece are crucial.
- As a guideline, a workpiece length-to-diameter ratio of up to 2:1 is normally acceptable for workpieces that are only supported on one end. If there is an additional tailstock support, this ratio can be extended.
- Use the Coromant Capto® system.
- Minimize all overhangs to maximize system rigidity.
- Always consider carbide bars for internal turning.




Wet or dry machining

Hard Part Turning (HPT) without coolant is the ideal situation, and is entirely feasible. Both CBN and ceramic inserts tolerate high cutting temperatures, which eliminate the costs and difficulties associated with coolants.

Some applications may require coolant, e.g. to control the thermal stability of the workpiece. In such cases, ensure a continuous flow of coolant throughout the entire turning operation.

Generally, the heat generated when machining is distributed into the chip (80%), workpiece (10%) and insert (10%). This shows the importance to evacuate the chips from the cutting-edge zone.




Cutting data and wear

High heat in the cutting-edge zone reduces the cutting forces. Therefore, a cutting speed that is too low generates less heat and can cause insert breakage.

Crater wear gradually affects the insert strength, but does not affect the surface finish as much.


In contrast, flank wear gradually affects the dimensional tolerance.



Insert change criteria

Predetermined surface finish is a frequent and practical insert change criterion. Surface finish is automatically measured in a separate station and a value is given to a specified finish quality.

When this set value is reached, it is time to change the tool. Set the predetermined number of components to 10–20% less than the average tool life of an optimized process. The exact figure will need to be determined on a case-to-case basis.



One- or two-cut strategy

When deciding between a one- or a two-cut strategy, these factors must be considered:


- Machine capability
- What the most important process measures are

It is very often a balance between accuracy and productivity.


One-cut strategy

With a high quality machine tool and a stable setup, a single cut can produce acceptable levels of surface quality and dimensional tolerance.

One-cut strategy



Two-cut strategy



Two-cut strategy

When the machine setup is unstable, if there is any inconsistency in the component or if a very high final tolerance or surface quality is required, a two-cut strategy is likely to be the best option.



Choose the right tool

External turning

Longitudinal and facing

Grooving, threading and profiling



B



Internal turning

Longitudinal, profiling and threading



C



D

Choose the right grade

Our CBN grade assortment consists of uncoated and PVD-coated inserts for various machining conditions. Use the information below to find the right grade for your application



CB7105 (H05)

First-choice CBN grade for low feed and continuous cuts in stable conditions at highest speed in case and induction hardened steels.



CB7115 (H15)

First-choice CBN grade for high feed and/or depth of cut in continuous to light interrupted cuts at high speed in case and induction hardened steels.



CB7125 (H25)

First choice CBN-grade designed to deliver stable and predictable tool life while machining case and induction hardened steels with light to medium interrupted cuts (chamfered component edges).




CB7135 (H35)

First choice CBN-grade designed to deliver stable and predictable tool life while machining case and induction hardened steels with heavy interrupted cuts (un-chamfered component edges).



CB7015 (H10)

CBN grade with low CBN content. Use in continuous cuts to light interrupted at high speed in case and induction hardened steels




CB7025 (H20)

CBN grade for medium to light interruptions and continuous cuts at medium speeds in case and induction hardened steels



CB7525 (H30)

CBN grade designed for grey cast iron machining and heavy interrupted hard part turning at low to medium speed.




CB7925 (H35)

Solid CBN grade originally designed for high alloyed cast iron but also works as a complement in hardened steels with bigger depth of cut or higher feed at low to medium speed.

Choose the right geometry

The insert geometry and edge preparation are extremely important in hard part turning as they have a significant influence on tool life and productivity. The Sandvik Coromant CBN product range includes inserts with standard nose radius, wipers and the unique Xcel design. The standard nose radius generates the lowest cutting forces and has the lowest stability requirements while wipers and Xcel give an unbeatable combination of high productivity and excellent surface finish.


Edge condition: There are four edge conditions available in the Sandvik Coromant CBN range:




Insert corner geometry

1. Radius - For poor to stable conditions
2. WH / WG - For improved surface finish or increased feed at average to stable conditions
3. Xcel (XA) - For high productivity at stable conditions
4. XB - Geometry for highest feed rate or best surface finish tolerances with normal feed rate at stable conditions


The Xcel geometry is a good complement for finishing. It has a straight cutting edge with a low entry angle which helps in producing thinner chips and lower cutting temperatures, reducing crater wear development and increasing feed capacity.




1. Standard radius



2. Wiper



3. Xcel



4. -XB geometry

Edge preparations



The strength of the cutting edge increases with increasing chamfer angle and width. A wide chamfer spreads the cutting forces over a larger area, which provides a more robust cutting edge, allowing for higher feed rates.

If surface finish and dimensional accuracy are the main requirements, a small chamfer will provide the best results.

Cutting forces and temperature will be reduced and therefore pose less risk for vibration.

Apply first choice edge preparation or strong edge preparation if long tool life and/or process security is of most importance.

Chamfer width



Edge preparations CB7015 and CB7025

Product family	T-Max® P		CoroTurn® 107		CoroTurn® TR	
	CB7015	CB7025	CB7015	CB7025	CB7015	CB7025
Grade	CB7015	CB7025	CB7015	CB7025	CB7015	CB7025
First choice	S01030	S01030	S01020	S01020	S01020	S01020
WH/WG	S01030 T01030	S01030	S01020 T01020 T01030	S01020 S01530 T01030	-	-
XA	S01515	S01515	S01515	S01515	-	-
Light	E F	S01020	T01020	-	-	-
Strong	S02035	S02035	S01530 T01030	S01530 T01030	-	-

Edge preparations CB7525

Product family	T-Max® P / T-Max®		CoroTurn® 107
	CB7525	CB7525	CB7525
Grade	CB7525	CB7525	CB7525
First choice	S01530	S01530	S01030
WH/WG	T01020	-	-
XA	-	-	-
Light	T01020	T01020	T01020
Strong	S02035	S02035	S01530

Edge preparations CB7105 and CB7115

Product family	T-Max® P		CoroTurn® 107		CoroTurn® TR		CoroCut® 1-2	
	CB7105	CB7115	CB7105	CB7115	CB7105	CB7115	CB7105	CB7115
Grade	CB7105	CB7115	CB7105	CB7115	CB7105	CB7115	CB7105	CB7115
First choice	S01525	S01525	S01020	S01020	S01020	S01020	-	-
WH/WG	S01520	S01520	S01520	S01520	-	-	-	-
XA	S01515	S01515	S01515	S01515	-	-	-	-
XB	-	-	-	-	-	-	S01025	S01025
Light	S01020	-	-	-	-	-	-	-
Strong	-	S02030	-	S02030	-	-	-	-

Edge preparations CB7125 and CB7135

Product family	T-Max® P		CoroTurn® 107		CoroTurn® TR	
	CB7125	CB7135	CB7125	CB7135	CB7125	CB7135
Grade	CB7125	CB7135	CB7125	CB7135	CB7125	CB7135
First choice	S01525	S01530	S01020	S01530	S01020	-
WH/WG	S01230*	-	T01020	-	-	-
XA	S01515	-	S01515	-	-	-
Light	S01025	S01025	-	-	-	-
Strong	S02035	-	S02030	-	-	-

* = HGR

Cutting data recommendations for CB7015 / CB7025 / CB7525 / CB7925

Valid for H1.3.Z.HA

Grade	CB7015		CB7025		CB7525		CB7925	
	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)
v_c m/min (ft/min)	120-220	(394-722)	90-150	(295-492)	80-150	(262-492)	60-110	(197-361)
f_r mm/rev (inch/rev)	0.05-0.25	(.002-.010)	0.05-0.25	(.002-.010)	0.05-0.3	(.002-.012)	0.1-0.40	(.004-.016)
f_r WH/WG mm/rev (inch/rev)	0.05-0.35	(.002-.014)	0.05-0.35	(.002-.014)	0.05-0.35	(.002-.014)	-	-
f_r Xcel - T-max P mm/rev (inch/rev)	0.25-0.45	(.010-.018)	0.25-0.45	(.010-.018)	-	-	-	-
f_r Xcel - CoroTurn 107 mm/rev (inch/rev)	0.15-0.40	(.006-.016)	0.15-0.40	(.006-.016)	-	-	-	-
f_r HGR mm/rev (inch/rev)	-	-	0.08-0.25	(.003-.010)	-	-	-	-
a_p mm (inch)	0.05-0.3	(.001-.012)	0.05-0.3	(.002-.012)	0.05-0.3	(.001-.012)	0.3-0.6	(.012-.016)
a_p Xcel - T-max P mm (inch)	0.15-0.25	(.006-.010)	0.15-0.25	(.006-.010)	-	-	-	-
a_p Xcel - CoroTurn 107 mm (inch)	0.05-0.20	(.002-.008)	0.05-0.20	(.002-.008)	-	-	-	-
a_p HGR mm (inch)	-	-	0.8-2.0	(.003-.008)	-	-	-	-

Cutting data recommendations for CB7105 / CB7115 / CB7125 / CB7135

Valid for H1.3.Z.HA

Grade	CB7105		CB7115		CB7125		CB7135	
	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)	v_c m/min (ft/min)	f_r mm/rev (inch/rev)
v_c m/min (ft/min)	150-250	(492-820)	120-220	(394-722)	100-200	(262-492)	80-160	(262-524)
f_r mm/rev (inch/rev)	0.05-0.15	(.002-.006)	0.05-0.25	(.002-.010)	0.05-0.3	(.002-.012)	0.05-0.40	(.002-.016)
f_r WH/WG mm/rev (inch/rev)	0.05-0.25	(.002-.010)	0.05-0.35	(.002-.014)	0.05-0.35	(.002-.014)	0.05-0.35	(.002-.014)
f_r Xcel - T-max P mm/rev (inch/rev)	0.25-0.40	(.010-.016)	0.25-0.45	(.010-.018)	0.25-0.45	(.010-.018)	-	-
f_r Xcel - CoroTurn 107 mm/rev (inch/rev)	0.15-0.35	(.006-.014)	0.15-0.40	(.006-.016)	0.15-0.40	(.006-.016)	-	-
f_r XB - CoroCut 1-2 mm/rev (inch/rev)	0.4-1.2	(.016-.047)	0.4-1.2	(.016-.047)	-	-	-	-
f_r HGR mm/rev (inch/rev)	-	-	-	-	0.08-0.25	(.003-.010)	-	-
a_p mm (inch)	0.05-0.25	(.002-.010)	0.05-0.3	(.002-.012)	0.05-0.5	(.002-.020)	0.05-0.5	(.002-.02)
a_p Xcel - T-max P mm (inch)	0.15-0.20	(.006-.008)	0.15-0.25	(.006-.010)	0.15-0.25	(.006-.010)	-	-
a_p Xcel - CoroTurn 107 mm (inch)	0.05-0.15	(.002-.006)	0.05-0.20	(.002-.008)	0.05-0.20	(.002-.008)	-	-
a_p XB - CoroCut 1-2 mm (inch)	0.08-0.12	(.003-.005)	0.08-0.12	(.003-.005)	-	-	-	-
a_p HGR mm (inch)	-	-	-	-	0.8-2.0	(.003-.080)	-	-

General turning	A
Parting and grooving	B
Thread turning	C
General information	D


General turning

CoroTurn® TR

CoroTurn® 107

CoroTurn® 111

Xcel geometry




TR-DC..	TR-VB..	CC..	CC..	DC..	SC..	TC..	VB..	TP..
A3	A4	A6	A8	A9	A10	A11	A12	A13

Page

T-Max® P

Xcel geometry




CN..	CN..	DN..	RN..	SN..	TN..	VN..	WN..
A16	A18	A20	A22	A24	A26	A27	A28

Page

T-Max®

CoroTurn® XS



CN..	RN..	SN..	CXS..
A31	A32	A33	A35

Page

Parting and grooving

CoroCut® 1-2
Grooving


Profiling

Turning

CoroTurn® XS
Grooving

CoroCut® MB
Grooving

Turning



123-GE/S	123-S	123-RE	123-S	CXS..	MB..R	MB..T093
B3	B5	B6	B7	B9	B11	B12

Page

Thread turning

CoroThread® 266

CoroTurn® XS

CoroCut® MB

V-profile 60° Non-topping

V-profile 60° Non-topping

Metric 60° Full form



266RG/RL	CXS..	MB..R
C3	C5	C7

Page

General turning

CoroTurn® TR	A2
Inserts	A3-A4
CoroTurn® 107	A5
Inserts	A6-A12
CoroTurn® 111	
Inserts	A13
T-Max® P	A14
Inserts	A15-A29
T-Max®	A30
Inserts	A31-A33
CoroTurn® XS	A34
Cutting tools	A35
CoroCut® 1-2	
Inserts	B7
CoroCut® MB	
Cutting tools	B12
CoroThread® 266	
Inserts	C3

CoroTurn® TR


For stable external and internal profiling

Application

- Profiling
- Medium to finishing

Benefits and features

- Stable insert clamping (iLock) ensures good repeatability and accuracy while allowing for high cutting data
- Precision coolant improves chip control and tool life
- Easy coolant connection and tool changes with plug and play adaptors or QS stops (QS shanks)




www.sandvik.coromant.com/coroturntr

iLock™ locking interface

The T-rail on the holder and corresponding groove on the insert lock the insert precisely and securely.


- High stability and tolerances
- High indexing repeatability



A3

CoroTurn® TR insert for turning

D-style insert (Rhombic 55°)



	LE	S	RE	GB	BN	ISO CODE	H					
							7015	7025	7105	7115	7125	
Finishing	13	3.1	5.53	0.4	20°	0.10	TR-DC1304S01020F	☆	★	☆	☆	
		.122	.218	.016	20°	.004						
		3.1	5.53	0.8	20°	0.10	TR-DC1308S01020F	☆	☆	☆	☆	★
		.122	.218	.031	20°	.004						




D2



D6

CoroTurn® TR insert for turning

V-style insert (Rhombic 35°)



	LE	S	RE	GB	BN	ISO CODE	H					
							7015	7025	7105	7125		
Finishing	13	3.1	4.53	0.4	20°	0.10	TR-VB1304S01020F	☆	☆	☆	☆	★
		.122	.178	.016	20°	.004						
		3.1	4.53	0.8	20°	0.10	TR-VB1308S01020F	☆	★	☆	☆	
		.122	.178	.031	20°	.004						



CoroTurn® 107

For internal and external turning of slender components

Application

- Longitudinal turning
- Profiling
- Back boring
- Medium to finishing

Benefits and features

- Low cutting forces
- Screw clamping ensures stability and unobstructed chip flow
- Insert geometries and grades for all materials
- Wiper geometries available for high feeds and excellent surface finish
- Holders and insert geometries with conventional and CoroTurn HP design



www.sandvik.coromant.com/coroturn107

Positive insert shape

- 5°, 7° clearance angle
- All types of insert shapes and sizes
- Geometries and grades for all application areas
- Insert grades also in advanced cutting materials PCD, CBN and ceramics


Tools

- Coromant Capto® cutting units
- Shank tools
- QS Shank tools
- Boring bars
- CoroTurn® SL heads

Tools with EasyFix™ and Silent Tools™ available.


Designed for precision coolant

HOLDERS are available with precision nozzles for excellent chip control.



Screw clamping

Adds stability and unobstructed chip flow





A6



D3

CoroTurn® 107 insert for turning

C-style insert (Rhombic 80°)



B

	LE	S	RE	BS	GB	BN	ISO CODE	K						H						ANSI CODE				
								7625	7015	7025	7105	7115	7125	7135	7625	7015	7025	7105	7115		7125	7135	7625	
Finishing	06	1/4	2.4	2.38	0.2	20°	0.10	CCGW060202S01020F						*										CCGW2(1.5)0S0320F
			.095	.094	.008	20°	.004	CCGW060202T01020F							*									CCGW2(1.5)0T0320F
			2.6	2.38	0.2	20°	0.10	CCGW060202T01030F																CCGW2(1.5)0T0330F
			.102	.094	.008	20°	.004	CCGW060204S01020F		*	*				*									CCGW2(1.5)1S0320F
			1.5	2.38	0.2	30°	0.10	CCGW060204S01030F		*	*				*									CCGW2(1.5)1S0330F
			.059	.094	.008	30°	.004	CCGW060204S01530F		*	*	*	*	*	*									CCGW2(1.5)1S0530F
			2.6	2.38	0.4	20°	0.10	CCGW060204T01020F		*	*	*	*	*	*									CCGW2(1.5)1T0320F
			.102	.094	.016	20°	.004	CCGW060204T01030F		*	*	*	*	*	*									CCGW2(1.5)1T0330F
			2.8	2.38	0.4	30°	0.10	CCGW060208S01020F							*									CCGW2(1.5)2S0320F
			.110	.094	.016	30°	.004	CCGW060208S01030F							*									CCGW2(1.5)2S0330F
			2.6	2.38	0.4	30°	0.15	CCGW060208T01020F							*									CCGW2(1.5)2T0320F
			.102	.094	.016	30°	.006	CCGW060208T01030F							*									CCGW2(1.5)2T0330F
			2.8	2.38	0.4	20°	0.10	CCGW060204S01520FWH	*															CCGW2(1.5)1S0520FWH
			.110	.094	.016	20°	.004	CCGW060204T01030FWH		*	*				*									CCGW2(1.5)1T0330FWH
			1.8	2.38	0.4	30°	0.10	CCGW060208S01520FWH							*	*								CCGW2(1.5)2S0520FWH
			.071	.094	.016	30°	.004	CCGW060208T01030FWH							*	*								CCGW2(1.5)2T0330FWH
			2.6	2.38	0.8	20°	0.15	CCGW060208T01030FWH							*	*								CCGW2(1.5)2T0330FWH
			.102	.094	.031	.022	20°	.006	CCGW060208T01030FWH		*	*				*	*							CCGW2(1.5)2T0330FWH
			2.0	2.38	0.8	0.6	30°	0.10	CCGW060208T01030FWH		*	*				*	*							CCGW2(1.5)2T0330FWH
			.079	.094	.031	.022	30°	.004	CCGW060208T01030FWH		*	*				*	*							CCGW2(1.5)2T0330FWH



C

D



CoroTurn® 107 insert for turning

C-style insert (Rhombic 80°)



	LE	S	RE	BS	GB	BN	ISO CODE	K						H						ANSI CODE										
								7825	7015	7025	7105	7115	7125	7135	7825	7015	7025	7105	7115		7125	7135	7825							
Finishing	09	3/8	2.6	3.97	0.4	20°	0.10	CCGW09T304S01020F		☆		☆					☆										CCGW3(2.5)1S0320F			
			.102	.156	.016	20°	.004					☆	☆													☆	☆	CCGW3(2.5)1S0630F		
			2.6	3.97	0.4	30°	0.15	CCGW09T304S01530F																			☆	☆	CCGW3(2.5)1S0830F	
			.102	.156	.016	30°	.006																					☆		CCGW3(2.5)1S0830F
			2.6	3.97	0.4	30°	0.20	CCGW09T304S02030F																				☆		CCGW3(2.5)1S0830F
			.102	.156	.016	30°	.008																							CCGW3(2.5)1T0320F
			2.8	3.97	0.4	20°	0.10	CCGW09T304T01020F	☆																			☆	CCGW3(2.5)1T0320F	
			.110	.156	.016	20°	.004																							CCGW3(2.5)2S0320F
			2.5	3.97	0.8	20°	0.10	CCGW09T308S01020F		☆	☆	☆	☆	☆	☆															CCGW3(2.5)2S0320F
			.098	.156	.031	20°	.004																							CCGW3(2.5)2S0630F
			2.5	3.97	0.8	30°	0.15	CCGW09T308S01530F		☆	☆																	☆	☆	CCGW3(2.5)2S0630F
			.098	.156	.031	30°	.006																							CCGW3(2.5)2S0830F
			2.5	3.97	0.8	30°	0.20	CCGW09T308S02030F																				☆	☆	CCGW3(2.5)2S0830F
			.098	.156	.031	30°	.008																							CCGW3(2.5)2T0320F
			3.0	3.97	0.8	20°	0.10	CCGW09T308T01020F	☆																			☆	CCGW3(2.5)2T0320F	
			.118	.156	.031	20°	.004																							CCGW3(2.5)3S0320F
			2.4	3.97	1.2	20°	0.10	CCGW09T312S01020F		☆		☆	☆	☆	☆															CCGW3(2.5)3S0320F
			.094	.156	.047	20°	.004																							CCGW3(2.5)3S0630F
			2.3	3.97	1.2	30°	0.15	CCGW09T312S01530F				☆																		CCGW3(2.5)3S0630F
			.091	.156	.047	30°	.006																							CCGW3(2.5)1S0320FWH
			2.4	3.97	1.2	0.6	20°	0.15	CCGW09T304S01020FWH				☆																	CCGW3(2.5)1S0520FWH
			.095	.156	.047	.024	20°	.006																						CCGW3(2.5)1S0520FWH
			2.6	3.97	0.4	0.5	20°	0.15	CCGW09T304S01520FWH				☆	☆	☆															CCGW3(2.5)1S0630FWH
			.102	.156	.016	.018	20°	.006																						CCGW3(2.5)1T0320FWH
			1.8	3.97	0.4	0.5	30°	0.15	CCGW09T304S01530FWH				☆																	CCGW3(2.5)1T0320FWH
			.071	.156	.016	.018	30°	.006																						CCGW3(2.5)2S0320FWH
			1.8	3.97	0.4	0.5	20°	0.10	CCGW09T304T01020FWH	☆																				CCGW3(2.5)2S0320FWH
			.071	.156	.016	.018	20°	.004																						CCGW3(2.5)2S0520FWH
			2.0	3.97	0.8	0.6	20°	0.10	CCGW09T308S01020FWH				☆																	CCGW3(2.5)2T0320FWH
			.079	.156	.031	.022	20°	.004																						CCGW3(2.5)2S0520FWH
			2.5	3.97	0.8	0.6	20°	0.15	CCGW09T308S01520FWH				☆	☆	☆															CCGW3(2.5)2T0320FWH
			.098	.156	.031	.022	20°	.006																						CCGW3(2.5)3S0320FWH
			2.0	3.97	0.8	0.6	20°	0.10	CCGW09T308T01020FWH	☆																				CCGW3(2.5)3S0320FWH
		.079	.156	.031	.022	20°	.004																						CCGW3(2.5)3S0320FWH	
		2.3	3.97	1.2	0.6	20°	0.10	CCGW09T312S01020FWH	☆																				CCGW3(2.5)3S0320FWH	
		.091	.156	.047	.024	20°	.004																						CCGW3(2.5)3S0320FWH	
		2.4	3.97	1.2	0.6	20°	0.15	CCGW09T312S01520FWH				☆	☆																CCGW3(2.5)3S0320FWH	
		.095	.156	.047	.024	20°	.006																							

B



C

D



CoroTurn® 107 insert for turning

C-style insert (Rhombic 80°)



	LE		S	REEQ	APMX	GB	BN	ISO CODE	H				
	09	3/8							7015	7025	7105	7115	7125
Finishing			2.3	3.97	1.9	0.2	15°	0.15	★	★	★	★	★
			.091	.156	.075	.008	15°	.006					



D2




D3



D6

CoroTurn® 107 insert for turning

D-style insert (Rhombic 55°)



	LE	S	RE	BS	GB	BN	ISO CODE	K							ANSI CODE				
								7525	7015	7025	7105	7115	7125	7135		7525	CB20		
Finishing	07	1/4	2.5	2.38	0.2	20°	0.10	DCGW070202S01020F										DCGW2(1.5)0S0320F	
			.098	.094	.008	20°	.004											DCGW2(1.5)0T0320F	
			2.5	2.38	0.2	20°	0.10	DCGW070202T01020F										DCGW2(1.5)1S0320F	
			.098	.094	.008	20°	.004											DCGW2(1.5)1S0330F	
			1.5	2.38	0.2	30°	0.10	DCGW070202T01030F		*	*							DCGW2(1.5)1S0320F	
			.059	.094	.008	30°	.004											DCGW2(1.5)1S0330F	
			2.9	2.38	0.4	20°	0.10	DCGW070204S01020F			*	*	*	*				DCGW2(1.5)1S0320F	
			.114	.094	.016	20°	.004											DCGW2(1.5)1S0330F	
			2.9	2.38	0.4	30°	0.10	DCGW070204S01030F		*	*					*		DCGW2(1.5)1S0530F	
			.114	.094	.016	30°	.004											DCGW2(1.5)1T0320F	
			2.9	2.38	0.4	30°	0.15	DCGW070204S01530F							*			DCGW2(1.5)2S0320F	
			.114	.094	.016	30°	.006											DCGW2(1.5)2S0330F	
			2.8	2.38	0.4	20°	0.10	DCGW070204T01020F	*							*		DCGW2(1.5)2S0320F	
			.110	.094	.016	20°	.004											DCGW2(1.5)2S0330F	
			2.5	2.38	0.8	20°	0.10	DCGW070208S01020F						*				DCGW2(1.5)2S0320F	
			.098	.094	.031	20°	.004			*	*							DCGW2(1.5)2S0330F	
			2.1	2.38	0.8	30°	0.10	DCGW070208S01030F		*	*							DCGW3(2.5)0T0320F	
			.083	.094	.031	30°	.004											DCGW3(2.5)1S0320F	
			11	3/8	2.8	3.97	0.2	20°	0.10	DCGW11T302T01020F	*						*		DCGW3(2.5)1S0320F
			.110	.156	.008	20°	.004												DCGW3(2.5)1S0320F
		1.8	3.97	0.4	20°	0.10	DCGW11T304S01020F		*	*	*	*	*				DCGW3(2.5)1S0630F		
		.071	.156	.016	20°	.004			*	*							DCGW3(2.5)1S0830F		
		2.9	3.97	0.4	30°	0.15	DCGW11T304S01530F		*	*			*	*			DCGW3(2.5)1T0320F		
		.114	.156	.016	30°	.006											DCGW3(2.5)2S0320F		
		2.9	3.97	0.4	30°	0.20	DCGW11T304S02030F				*						DCGW3(2.5)2S0630F		
		.113	.156	.016	30°	.008											DCGW3(2.5)2S0830F		
		2.9	3.97	0.4	20°	0.10	DCGW11T304T01020F	*	*						*		DCGW3(2.5)2T0320F		
		.114	.156	.016	20°	.004											DCGW3(2.5)2S0320F		
		2.5	3.97	0.8	20°	0.10	DCGW11T308S01020F		*	*	*	*	*				DCGW3(2.5)2S0630F		
		.098	.156	.031	20°	.004			*	*							DCGW3(2.5)2S0830F		
		3.1	3.97	0.8	30°	0.15	DCGW11T308S01530F		*	*			*	*			DCGW3(2.5)2T0320F		
		.122	.156	.031	30°	.006											DCGW3(2.5)2S0320F		
		2.5	3.97	0.8	30°	0.20	DCGW11T308S02030F				*	*					DCGW3(2.5)3S0320F		
		.098	.156	.031	30°	.008					*	*					DCGW3(2.5)3S0630F		
		3.1	3.97	0.8	20°	0.10	DCGW11T308T01020F	*	*						*		DCGW3(2.5)3S0320F		
		.122	.156	.031	20°	.004			*	*							DCGW3(2.5)3S0630F		
		2.1	3.97	1.2	20°	0.10	DCGW11T312S01020F		*	*	*	*					DCMW3(2.5)1S0320E		
		.083	.156	.047	20°	.004											DCMW3(2.5)2S0320E		
		2.4	3.97	1.2	30°	0.15	DCGW11T312S01530F	*									DCMW3(2.5)2S0320E		
		.094	.156	.047	30°	.006											DCGW3(2.5)1S0320FWH		
		3.7	3.97	0.4	20°	0.10	DCMW11T304S01020E								*		DCGW3(2.5)1S0520FWH		
		.144	.156	.016	20°	.004											DCGW3(2.5)1S0520FWH		
		3.4	3.97	0.8	20°	0.10	DCMW11T308S01020E								*		DCGW3(2.5)2S0320FWH		
		.132	.156	.031	20°	.004											DCGW3(2.5)2S0320FWH		
		1.8	3.97	0.4	0.5	20°	0.10	DCGW11T304S01020FWH		*	*						DCGW3(2.5)2S0320FWH		
		.071	.156	.016	.018	20°	.004				*	*					DCGW3(2.5)2S0520FWH		
		2.9	3.97	0.4	0.5	20°	0.15	DCGW11T304S01520FWH		*	*						DCGW3(2.5)2S0320FWH		
		.113	.156	.016	.018	20°	.006										DCGW3(2.5)2S0520FWH		
		2.1	3.97	0.8	0.6	20°	0.10	DCGW11T308S01020FWH		*	*				*		DCGW3(2.5)2S0520FWH		
		.083	.156	.031	.022	20°	.004				*	*					DCGW3(2.5)2S0520FWH		
		2.5	3.97	0.8	0.6	20°	0.15	DCGW11T308S01520FWH			*	*							
		.098	.156	.031	.022	20°	.006												

B



C

D



CoroTurn® 107 insert for turning

S-style insert (Square)



B

	IC		LE	S	RE	GB	BN	ISO CODE	H			ANSI CODE
	09	3/8							7015	7025	7625	
Finishing			1.8	3.97	0.4	30°	0.10	SCGW09T304S01030F	☆	★		SCGW3(2.5)1S0330F
			.071	.156	.016	30°	.004					
			2.8	3.97	0.4	20°	0.10	SCGW09T304T01020F			★	SCGW3(2.5)1T0320F
			.110	.156	.016	20°	.004					
			2.1	3.97	0.8	30°	0.10	SCGW09T308S01030F	☆	★		SCGW3(2.5)2S0330F
			.083	.156	.031	30°	.004					
			3.1	3.97	0.8	30°	0.15	SCGW09T308S01530F			★	SCGW3(2.5)2S0630F
			.122	.156	.031	30°	.006					
		3.1	3.97	0.8	20°	0.10	SCGW09T308T01020F			★	SCGW3(2.5)2T0320F	
		.122	.156	.031	20°	.004						



C

D



CoroTurn® 107 insert for turning

T-style insert (Triangular)




	LE	S	RE	GB	BN	ISO CODE	K							H							ANSI CODE						
							7525	7015	7025	7105	7115	7125	7135	7525	CB20	7525	7015	7025	7105	7115		7125	7135	7525	CB20		
Finishing	06	5/32	2.0	1.59	0.2	20°	0.10	TCGW06T102S01020E																			TCGW1.2(1.2)0S0320E
			.077	.063	.008	20°	.004	TCGW06T102T01020E																			TCGW1.2(1.2)0T0320E
			1.5	1.98	0.2	20°	0.10	TCGW06T104S01020E																			TCGW1.2(1.2)1S0320E
			.059	.078	.008	20°	.004	TCGW06T104S01020E																			TCGW1.2(1.2)1S0320E
			1.8	1.98	0.4	20°	0.10	TCGW06T104S01020E																			TCGW1.2(1.2)1S0320E
			.071	.078	.016	20°	.004	TCGW090202S01020F																			TCGW1.8(1.5)0S0320F
			1.8	2.38	0.2	20°	0.10	TCGW090202T01020F																			TCGW1.8(1.5)0T0320F
			.071	.094	.008	20°	.004	TCGW090204S01020F																			TCGW1.8(1.5)1S0320F
			2.5	2.38	0.2	20°	0.10	TCGW090204S01020F																			TCGW1.8(1.5)1S0320F
			.098	.094	.008	20°	.004	TCGW090204S01030F																			TCGW1.8(1.5)1S0330F
			1.8	2.38	0.4	20°	0.10	TCGW090204S01030F																			TCGW1.8(1.5)1S0330F
			.071	.094	.016	30°	.004	TCGW090204S01530F																			TCGW1.8(1.5)1S0630F
			2.8	2.38	0.4	30°	0.15	TCGW090204S01530F																			TCGW1.8(1.5)1S0630F
			.110	.094	.016	30°	.006	TCMW090204S01020E																			TCMW1.8(1.5)1S0320E
			3.0	2.38	0.4	20°	0.10	TCMW090204S01020E																			TCMW1.8(1.5)1S0320E
			.118	.094	.016	20°	.004	TCGW110202T01020F																			TCGW2(1.5)0T0320F
			2.8	2.38	0.2	20°	0.10	TCGW110204S01020F																			TCGW2(1.5)1S0320F
			.110	.094	.008	20°	.004	TCGW110204S01530F																			TCGW2(1.5)1S0630F
			1.8	2.38	0.4	30°	0.15	TCGW110204T01020F																			TCGW2(1.5)1T0320F
			.071	.094	.016	30°	.006	TCGW110208S01020F																			TCGW2(1.5)2S0320F
			2.8	2.38	0.4	20°	0.10	TCGW110208S01530F																			TCGW2(1.5)2S0630F
			.110	.094	.016	20°	.004	TCGW110304S01020F																			TCGW221S0320F
			2.9	2.38	0.8	20°	0.10	TCGW110304S01530F																			TCGW221S0630F
			.114	.125	.031	20°	.004	TCGW110304S01530F																			TCGW221S0630F
		2.0	2.38	0.8	30°	0.15	TCGW110304T01020F																			TCGW221T0320F	
		.079	.094	.031	30°	.006	TCGW110308S01020F																			TCGW222S0320F	
		1.8	3.18	0.4	20°	0.10	TCGW110308S01530F																			TCGW222S0630F	
		.114	.125	.031	30°	.006	TCGW110308T01020F																			TCGW222T0320F	
		2.9	3.18	0.8	20°	0.10	TCMW110204S01020E																			TCMW2(1.5)1 S0320E	
		.114	.125	.031	20°	.004	TCMW110208S01020E																			TCMW2(1.5)2S0320E	
		3.0	2.38	0.4	20°	0.10	TCMW110304S01020E																			TCMW221S0320E	
		.118	.094	.016	20°	.004	TCMW110308S01020E																			TCMW222S0320E	
		3.0	3.18	0.4	20°	0.10	TCMW110308S01020E																			TCMW222S0320E	
		.118	.125	.031	20°	.004	TCMW110308S01020E																			TCMW222S0320E	

B


C

D



CoroTurn® 107 insert for turning

V-style insert (Rhombic 35°)



	LE	S	RE	GB	BN	ISO CODE	K							H							ANSI CODE					
							7525	7015	7025	7105	7115	7125	7135	7525	CB20	7525	7015	7025	7105	7115		7125	7135	7525	CB20	
Finishing	11	1/4	2.5	3.18	0.2	20°	0.10	VBGW110302S01020F						*												VBGW220T0320F
			.098	.125	.008	20°	.004							*												VBGW220T0320F
			2.3	3.18	0.2	20°	0.10	VBGW110302T01020F						*												VBGW220T0320F
			.091	.125	.008	20°	.004							*												VBGW221S0320F
			2.5	3.18	0.4	20°	0.10	VBGW110304S01020F		*	*	*	*	*				*	*							VBGW221T0530F
			.098	.125	.016	20°	.004											*	*							VBGW221T0530F
			2.5	3.18	0.4	30°	0.15	VBGW110304S01530F										*	*							VBGW331S0320F
			.098	.125	.016	30°	.006											*	*							VBGW331S0330F
			.118	.188	.016	30°	.004							*												VBGW331S0630F
			4.0	4.76	0.4	20°	0.10	VBGW160404T01020F	*										*	*						VBGW331T0320F
			.157	.188	.016	20°	.004																			VBGW332S0320F
			3.0	4.76	0.8	20°	0.10	VBGW160408S01020F		*	*	*	*	*												VBGW332S0630F
		.118	.188	.031	20°	.004							*												VBGW332T0320F	
		2.5	4.76	0.8	30°	0.15	VBGW160408S01530F		*	*							*	*							VBGW331S0320E	
		.098	.188	.031	30°	.006											*	*							VBGW332T0320F	
		4.0	4.76	0.8	20°	0.10	VBGW160408T01020F	*										*	*						VBMW331S0320E	
		.157	.188	.031	20°	.004																			VBMW332S0320E	
		4.7	4.76	0.4	20°	0.10	VBMW160404S01020E															*				
		.185	.188	.016	20°	.004																*				
		4.1	4.76	0.8	20°	0.10	VBMW160408S01020E															*				
		.162	.188	.031	20°	.004																*				



D2





D3



D6

CoroTurn® 111 insert for turning

T-style insert (Triangular)



	11	1/4	LE	S	RE	GB	BN	ISO CODE	H			ANSI CODE
									7015	7025	7105	
Finishing			1.8	3.18	0.4	20°	0.10	TPGW110304S01020F	☆	★	☆	TPGW221S0320F
			.071	.125	.016	20°	.004					
			2.0	3.18	0.8	20°	0.10	TPGW110308S01020F	☆	★	☆	TPGW222S0320F
			.079	.125	.031	20°	.004					




T-Max® P

Optimized for external turning

Application

- Longitudinal turning
- Face turning
- Profiling
- Roughing to finishing
- Internal turning of large diameter bores from dia 50 mm (2 inch)



Benefits and features

- Productive solution with Wiper and Xcel technologies
- Tools featuring precision coolant for excellent chip breaking
- Reliable and secure machining, even in roughing applications
- Double sided inserts with strong edges
- Lever clamping for wet machining, Rigid-clamping for dry machining and short chip materials, Wedge clamp for improved accessibility

B

C

www.sandvik.coromant.com/tmaxp

Inserts

- All types of insert shapes and sizes
- Geometries and grades for all application areas
- Insert grades also in advanced cutting materials PCD, CBN and ceramic
- Inserts dedicated for precision coolant

Tools

- Coromant Capto® cutting units
- Shank tools
- Boring bars
- CoroTurn® SL heads




Precision coolant

HOLDERS ARE AVAILABLE WITH PRECISION NOZZLES FOR EXCELLENT CHIP CONTROL.

Different clamping solutions

Lever clamping
Not recommended for HPT

Rigid clamping
Recommended for HPT



D





A16





D3

T-Max® P insert for turning

C-style insert (Rhombic 80°)



	LE		S	RE	BS	GB	BN	ISO CODE	H		ANSI CODE
	12	1/2							7/125	7/135	
Finishing			2.6	4.76	0.4	30°	0.15	CNGA120404S01530F			★ CNGA431S0530F
			.102	.188	.016	30°	.006				
			2.5	4.76	0.8	30°	0.15	CNGA120408S01530F			★ CNGA432S0530F
			.098	.188	.031	30°	.006				
			2.5	4.76	0.8	35°	0.20	CNGA120408S02035F			★ CNGA432S0835F
			.098	.188	.031	35°	.008				
			2.9	4.76	1.2	30°	0.15	CNGA120412S01530F			★ CNGA433S0530F
			.113	.188	.047	30°	.006				
			2.4	4.76	1.2	35°	0.20	CNGA120412S02035F			★ CNGA433S0835F
			.094	.188	.047	35°	.008				
			2.8	4.76	1.6	35°	0.20	CNGA120416S02035F			★ CNGA434S0835F
			.110	.188	.063	35°	.008				
			3.5	4.76	0.8	30°	0.12	CNGM120408F-HGR			★ CNGM432F-HGR
			.138	.188	.031	30°	.005				
		3.5	4.76	1.2	30°	0.12	CNGM120412F-HGR			★ CNGM433F-HGR	
		.138	.188	.047	30°	.005					
		2.5	4.76	0.8	0.6	20°	0.15	CNGA120408S01520FWH			★ CNGA432S0520FWH
		.098	.188	.031	.022	20°	.006				




	LE		S	RE	GB	BN	ISO CODE	H		ANSI CODE
	12	1/2						CR20		
Finishing			2.8	4.76	0.4	20°	0.10	CNMA120404S01020E		☆ CNMA431S0320E
			.110	.188	.016	20°	.004			
			2.8	4.76	0.8	20°	0.10	CNMA120408S01020E		☆ CNMA432S0320E
			.110	.188	.031	20°	.004			
			2.7	4.76	1.2	20°	0.10	CNMA120412S01020E		☆ CNMA433S0320E
		.106	.188	.047	20°	.004				



T-Max® P insert for turning

C-style insert (Rhombic 80°)





	LE	S	RE	BS	GB	BN	ISO CODE	K					H					ANSI CODE	
								7525	7015	7025	7105	7115	7125	7525	7015	7025	7105		7115
B	09	3/8	2.4	3.18	0.4	30°	0.10	CNGA090304S01030A		☆	★						CNGA321S0330A		
			.094	.125	.016	30°	.004												
	2.4	3.18	0.8	30°	0.10				☆	★							CNGA322S0330A		
	.094	.125	.031	30°	.004														
	2.0	3.18	0.8	35°	0.20						★						CNGA322S0835A		
	.079	.125	.031	35°	.008														
	2.4	3.18	0.4	0.5	30°	0.10					★						CNGA321S0330AWH		
	.094	.125	.016	.018	30°	.004													
	2.4	3.18	0.4	0.5	30°	0.10				★							CNGA321T0330AWH		
	.094	.125	.016	.018	30°	.004													
	2.4	3.18	0.8	0.6	30°	0.10					★						CNGA322S0330AWH		
	.094	.125	.031	.022	30°	.004													
	2.4	3.18	0.8	0.6	30°	0.10				★							CNGA322T0330AWH		
	.094	.125	.031	.022	30°	.004													
	C	12	1/2	1.8	4.76	0.4	20°	0.10	CNGA120404S01020A			★						CNGA431S0320A	
.071				.188	.016	20°	.004												
2.6				4.76	0.4	20°	0.10					★						CNGA431S0320H	
.102				.188	.016	20°	.004												
3.0				4.76	0.4	30°	0.10				☆	★							CNGA431S0330A
.118				.188	.016	30°	.004												
2.6				4.76	0.4	25°	0.15						☆	★	★				CNGA431S0525H
.102				.188	.016	25°	.006												
1.8				4.76	0.4	35°	0.20						★						CNGA431S0835A
.071				.188	.016	35°	.008												
3.1				4.76	0.4	35°	0.20				★						★		CNGA431S0835B
.122				.188	.016	35°	.008												
3.1				4.76	0.4	20°	0.10				★						★		CNGA431T0320B
.122				.188	.016	20°	.004												
2.9				4.76	0.8	18°	0.10					☆	★						CNGA432S0318A
.114		.188	.031	18°	.004														
2.5		4.76	0.8	20°	0.10							★					CNGA432S0320H		
.098		.188	.031	20°	.004														
2.9		4.76	0.8	30°	0.10					☆	★						CNGA432S0330A		
.114		.188	.031	30°	.004														
2.5		4.76	0.8	25°	0.15						☆	★	★				CNGA432S0525H		
.098		.188	.031	25°	.006														
2.1		4.76	0.8	30°	0.15										★		CNGA432S0630B		
.083		.188	.031	30°	.006														
2.5		4.76	0.8	30°	0.20								★				CNGA432S0830H		
.098		.188	.031	30°	.008														
2.9		4.76	0.8	35°	0.20					☆	★						CNGA432S0835A		
.114		.188	.031	35°	.008														
2.1		4.76	0.8	35°	0.20										★		CNGA432S0835B		
.083		.188	.031	35°	.008														
2.1	4.76	0.8	20°	0.10				★						★		CNGA432T0320B			
.083	.188	.031	20°	.004															
2.1	4.76	0.8	30°	0.10					★							CNGA432T0330A			
.083	.188	.031	30°	.004															
2.8	4.76	1.2	18°	0.10					☆	★						CNGA433S0318A			
.110	.188	.047	18°	.004															
2.4	4.76	1.2	20°	0.10							★					CNGA433S0320H			
.095	.188	.047	20°	.004															
2.8	4.76	1.2	30°	0.10					☆	★						CNGA433S0330A			
.110	.188	.047	30°	.004															
2.4	4.76	1.2	25°	0.15							☆	★	★			CNGA433S0525H			
.094	.188	.047	25°	.006															
2.4	4.76	1.2	30°	0.15										★		CNGA433S0630B			
.094	.188	.047	30°	.006															
2.4	4.76	1.2	30°	0.20								★				CNGA433S0830H			
.095	.188	.047	30°	.008															



T-Max® P insert for turning

C-style insert (Rhombic 80°)



	LE	S	RE	BS	GB	BN	ISO CODE	K					H					ANSI CODE		
								7525	7015	7025	7105	7115	7125	7525	7015	7025	7105		7115	7125
Finishing	12	1/2	2.8	4.76	1.2	35°	0.20	CNGA120412S02035A		☆	★						CNGA433S0835A			
			.110	.188	.047	35°	.008													
			2.4	4.76	1.2	35°	0.20	CNGA120412S02035B									★	CNGA433S0835B		
			.094	.188	.047	35°	.008													
			2.4	4.76	1.2	20°	0.10	CNGA120412T01020B	★									★	CNGA433T0320B	
			.094	.188	.047	20°	.004													
			2.4	4.76	1.2	30°	0.10	CNGA120412T01030A		★									CNGA433T0330A	
			.094	.188	.047	30°	.004													
			2.8	4.76	1.6	25°	0.10	CNGA120416S01025H							★				CNGA434S0325H	
			.110	.188	.063	25°	.004													
			2.7	4.76	1.6	30°	0.10	CNGA120416S01030A		☆	★								CNGA434S0330A	
			.106	.188	.063	30°	.004													
			2.3	4.76	1.6	25°	0.15	CNGA120416S01525H				☆	★						CNGA434S0525H	
			.092	.188	.063	25°	.006													
			2.7	4.76	1.6	35°	0.20	CNGA120416S02035A				★							CNGA434S0835A	
			.106	.188	.063	35°	.008													
			2.1	4.76	0.8			CNGA120408EA		★									CNGA432AA	
			.083	.188	.031															
			2.4	4.76	1.2			CNGA120412EA		★									CNGA433AA	
			.094	.188	.047															
			1.8	4.76	0.4	0.8	20°	0.10	CNGA120404T01020BWG	★								★	CNGA431T0320BWG	
			.071	.188	.016	.031	20°	.004												
			2.9	4.76	0.8	1.0	30°	0.10	CNGA120408S01030AWG		☆	★							CNGA432S0330AWG	
			.114	.188	.031	.039	30°	.004												
			2.5	4.76	0.8	0.6	20°	0.15	CNGA120408S01520HWG				☆	★	★				CNGA432S0520HWG	
			.098	.188	.031	.022	20°	.006												
			2.1	4.76	0.8	1.0	20°	0.10	CNGA120408T01020BWG	★									★	CNGA432T0320BWG
			.083	.188	.031	.039	20°	.004												
			2.8	4.76	1.2	1.2	30°	0.10	CNGA120412S01030AWG		☆	★							CNGA433S0330AWG	
			.110	.188	.047	.047	30°	.004												
			2.4	4.76	1.2	1.2	20°	0.15	CNGA120412S01520HWG				☆	★					CNGA433S0520HWG	
			.095	.188	.047	.047	20°	.006												
			3.0	4.76	0.4	0.5	30°	0.10	CNGA120404S01030AWH				★						CNGA431S0330AWH	
			.118	.188	.016	.018	30°	.004												
			2.6	4.76	0.4	0.5	20°	0.15	CNGA120404S01520HWH							★			CNGA431S0520HWH	
			.102	.188	.016	.018	20°	.006												
			3.0	4.76	0.4	0.5	30°	0.10	CNGA120404T01030AWH		★								CNGA431T0330AWH	
			.118	.188	.016	.018	30°	.004												
			2.9	4.76	0.8	0.6	30°	0.10	CNGA120408S01030AWH		☆	★							CNGA432S0330AWH	
			.114	.188	.031	.022	30°	.004												
		2.5	4.76	1.2	0.6	20°	0.15	CNGA120408S01520HWH				☆	★	★				CNGA432S0520HWH		
		.098	.188	.047	.022	20°	.006													
		2.1	4.76	0.8	0.6	35°	0.20	CNGA120408S02035AWH		☆	★							CNGA432S0835AWH		
		.083	.188	.031	.022	35°	.008													
		2.9	4.76	0.8	0.6	30°	0.10	CNGA120408T01030AWH		★								CNGA432T0330AWH		
		.114	.188	.031	.022	30°	.004													
		2.8	4.76	1.2	0.6	30°	0.10	CNGA120412S01030AWH			★							CNGA433S0330AWH		
		.110	.188	.047	.024	30°	.004													
		2.4	4.76	1.2	0.6	20°	0.15	CNGA120412S01520HWH				☆	★	★				CNGA433S0520HWH		
		.094	.188	.047	.024	20°	.006													
		2.8	4.76	1.2	0.6	30°	0.10	CNGA120412T01030AWH		★								CNGA433T0330AWH		
		.110	.188	.047	.024	30°	.004													

B


C

D



T-Max® P insert for turning

C-style insert (Rhombic 80°)



	LE		S	REEQ	APMX	GB	BN	ISO CODE	H				
	12	1/2							7015	7025	7105	7115	7125
Finishing			4.76	2.3	0.3	15°	0.15	CNGX1204L025-18AXA	☆	★			
			.188	.091	.010	15°	.006						
			3.3	4.76	2.3	0.3	15°	0.15	CNGX1204L025-18HXA		☆	★	★
			.128	.188	.091	.010	15°	.006					



D2





D3





D6

T-Max® P insert for turning

D-style insert (Rhombic 55°)



	LE	S	RE	GB	BN	ISO CODE	H		ANSI CODE		
							7125	7135			
Finishing	11	3/8	2.9	4.76	0.4	30°	0.15	DNGA110404S01530F	★	DNGA331S0530F	
			.114	.188	.016	30°	.006				
			2.5	4.76	0.8	30°	0.15	DNGA110408S01530F	★	DNGA332S0530F	
			.098	.188	.031	30°	.006				
		15	1/2	2.5	4.76	0.8	30°	0.15	DNGA150408S01530F	★	DNGA432S0530F
			.098	.188	.031	30°	.006				
			2.5	4.76	0.8	35°	0.20	DNGA150408S02035F	★	DNGA432S0835F	
			.098	.188	.031	35°	.008				
			3.2	4.76	1.2	30°	0.15	DNGA150412S01530F	★	DNGA433S0530F	
			.125	.188	.047	30°	.006				
			3.2	4.76	1.2	35°	0.20	DNGA150412S02035F	★	DNGA433S0835F	
			.125	.188	.047	35°	.008				
			3.5	4.76	0.8	30°	0.12	DNGM150408F-HGR	★	DNGM432F-HGR	
			.138	.188	.031	30°	.005				
		3.5	4.76	1.2	30°	0.12	DNGM150412F-HGR	★	DNGM433F-HGR		
		.138	.188	.047	30°	.005					



	LE	S	RE	GB	BN	ISO CODE	H		ANSI CODE	
							CE20			
Finishing	15	1/2	3.3	4.76	0.4	20°	0.10	DNMA150404S01020E	☆	DNMA431S0320E
			.130	.188	.016	20°	.004			
			2.9	4.76	0.8	20°	0.10	DNMA150408S01020E	☆	DNMA432S0320E
			.114	.188	.031	20°	.004			
			2.6	4.76	1.2	20°	0.10	DNMA150412S01020E	☆	DNMA433S0320E
		.102	.188	.047	20°	.004				



ENG


B

C

D

T-Max® P insert for turning

D-style insert (Rhombic 55°)



	LE	S	RE	BS	GB	BN	ISO CODE	K					H					ANSI CODE
								7525	7015	7025	7105	7115	7125	7525	7015	7025	7105	
B	11	3/8	1.8	4.76	0.4	20°	0.10	DNGA110404S01020A			★							DNGA331S0320A
			.071	.188	.016	20°	.004											
			3.2	4.76	0.4	30°	0.10	DNGA110404S01030A		☆	★							DNGA331S0330A
			.126	.188	.016	30°	.004											
			2.9	4.76	0.4	25°	0.15	DNGA110404S01525H				☆	★	★				DNGA331S0525H
			.114	.188	.016	25°	.006											
			1.8	4.76	0.4	20°	0.10	DNGA110404T01020B	★								★	DNGA331T0320B
			.071	.188	.016	20°	.004											
			2.1	4.76	0.8	20°	0.10	DNGA110408S01020A				★						DNGA332S0320A
			.083	.188	.031	20°	.004											
			2.8	4.76	0.8	30°	0.10	DNGA110408S01030A		☆	★							DNGA332S0330A
			.110	.188	.031	30°	.004											
			2.5	4.76	0.8	25°	0.15	DNGA110408S01525H				☆	★	★				DNGA332S0525H
			.098	.188	.031	25°	.006											
			1.8	4.76	0.8	35°	0.20	DNGA110408S02035A			★							DNGA332S0835A
			.071	.188	.031	35°	.008											
			2.1	4.76	0.8	20°	0.10	DNGA110408T01020B	★								★	DNGA332T0320B
			.083	.188	.031	20°	.004											
			2.5	4.76	1.2	30°	0.10	DNGA110412S01030A		★								DNGA333S0330A
			.098	.188	.047	30°	.004											
		2.1	4.76	1.2	25°	0.15	DNGA110412S01525H				☆	★					DNGA333S0525H	
		.084	.188	.047	25°	.006												
C	15	1/2	1.8	4.76	0.4	20°	0.10	DNGA150404S01020A			★							DNGA431S0320A
			.071	.188	.016	20°	.004											
			2.9	4.76	0.4	20°	0.10	DNGA150404S01020H				★						DNGA431S0320H
			.113	.188	.016	20°	.004											
			4.0	4.76	0.4	30°	0.10	DNGA150404S01030A		☆	★							DNGA431S0330A
			.157	.188	.016	30°	.004											
			2.9	4.76	0.4	25°	0.15	DNGA150404S01525H				☆	★	★				DNGA431S0525H
			.114	.188	.016	25°	.006											
			1.8	4.76	0.4	35°	0.20	DNGA150404S02035A			★							DNGA431S0835A
			.071	.188	.016	35°	.008											
			2.1	4.76	0.8	20°	0.10	DNGA150408S01020A			★							DNGA432S0320A
			.083	.188	.031	20°	.004											
			2.5	4.76	0.8	20°	0.10	DNGA150408S01020H				★						DNGA432S0320H
			.098	.188	.031	20°	.004											
			3.6	4.76	0.8	30°	0.10	DNGA150408S01030A		☆	★							DNGA432S0330A
			.142	.188	.031	30°	.004											
			2.5	4.76	0.8	25°	0.15	DNGA150408S01525H				☆	★	★				DNGA432S0525H
			.098	.188	.031	25°	.006											
			2.2	4.76	0.8	30°	0.15	DNGA150408S01530B									★	DNGA432S0630B
			.087	.188	.031	30°	.006											
		2.5	4.76	0.8	30°	0.20	DNGA150408S02030H					★					DNGA432S0830H	
		.098	.188	.031	30°	.008												
		2.1	4.76	0.8	35°	0.20	DNGA150408S02035A		☆	★							DNGA432S0835A	
		.083	.188	.031	35°	.008												
		2.1	4.76	1.2	20°	0.10	DNGA150412S01020H				★						DNGA433S0320H	
		.084	.188	.047	20°	.004												
		3.3	4.76	1.2	30°	0.10	DNGA150412S01030A		☆	★							DNGA433S0330A	
		.130	.188	.047	30°	.004												
		3.2	4.76	1.2	25°	0.15	DNGA150412S01525H				☆	★	★				DNGA433S0525H	
		.125	.188	.047	25°	.006												
		3.3	4.76	1.2	30°	0.15	DNGA150412S01530B										★	DNGA433S0630B
		.130	.188	.047	30°	.006												
		2.1	4.76	1.2	30°	0.20	DNGA150412S02030H					★					DNGA433S0830H	
		.084	.188	.047	30°	.008												
		2.4	4.76	1.2	35°	0.20	DNGA150412S02035A		☆	★							DNGA433S0835A	
		.094	.188	.047	35°	.008												
		2.9	4.76	1.6	30°	0.10	DNGA150416S01030A		☆	★							DNGA434S0330A	
		.114	.188	.063	30°	.004												



D2




D3



D6

T-Max® P insert for turning

D-style insert (Rhombic 55°)






	LE	S	RE	BS	GB	BN	ISO CODE	K					H					ANSI CODE			
								7525	7015	7025	7105	7115	7125	7525	7015	7025	7105		7115	7125	
Finishing	15	1/2	2.5	4.76	1.6	25°	0.15	DNGA150416S01525H												DNGA434S0525H	
			.098	.188	.063	25°	.006					☆	★	★							
			2.2	4.76	0.8			DNGA150408EA		★											DNGA432AA
			.087	.188	.031																
			2.5	4.76	1.2			DNGA150412EA		★											DNGA433AA
			.098	.188	.047																
			3.6	4.76	0.8	0.6	30°	0.10	DNGA150408S01030AWH		☆	★									DNGA432S0330AWH
			.142	.188	.031	.022	30°	.004													
			2.5	4.76	0.8	0.6	20°	0.15	DNGA150408S01520HWH				☆	★	★						DNGA432S0520HWH
			.098	.188	.031	.022	20°	.006													
			2.1	4.76	0.8	0.6	35°	0.20	DNGA150408S02035AWH				★								DNGA432S0835AWH
			.083	.188	.031	.022	35°	.008													
			3.3	4.76	1.2	0.6	30°	0.10	DNGA150412S01030AWH		☆	★									DNGA433S0330AWH
			.130	.188	.047	.024	30°	.004													
		2.1	4.76	1.2	0.6	20°	0.15	DNGA150412S01520HWH				☆	★							DNGA433S0520HWH	
		.084	.188	.047	.024	20°	.006														



T-Max® P insert for turning

R-style insert (Round)



							H		
							CB20		
							☆		
Medium			S	RE	GB	BN	ISO CODE	ANSI CODE	
	09	3/8	3.18	4.76	20°	0.10	RNGA090300S01020D	RNGA32S0320D	
		.125	.188	20°	.004				

B



C

D



T-Max® P insert for turning

S-style insert (Square)





	IC		LE	S	RE	GB	BN	ISO CODE	H				ANSI CODE	
	12	1/2							7105	7115	7125	7135		CB20
Finishing			2.5	4.76	0.8	25°	0.15	SNGA120408S01525F	☆	★				SNGA432S0525F
			.098	.188	.031	25°	.006							
			2.5	4.76	0.8	30°	0.15	SNGA120408S01530F				★		SNGA432S0530F
			.098	.188	.031	30°	.006							
			2.5	4.76	1.2	25°	0.15	SNGA120412S01525F	☆	★				SNGA433S0525F
			.098	.188	.047	25°	.006							
			2.8	4.76	1.2	30°	0.15	SNGA120412S01530F				★		SNGA433S0530F
			.110	.188	.047	30°	.006							
			2.8	4.76	1.6	25°	0.10	SNGA120416S01025F			★	☆		SNGA434S0325F
			.110	.188	.063	25°	.004							
			2.9	4.76	2.0	25°	0.10	SNGA120420S01025F			★			SNGA435S0325F
			.114	.188	.079	25°	.004							
		2.8	4.76	2.4	25°	0.10	SNGA120424S01025F			★	☆		SNGA436S0325F	
		.110	.188	.094	25°	.004								
		3.4	4.76	0.8	20°	0.10	SNMA120408S01020E					☆	SNMA432S0320E	
		.134	.188	.031	20°	.004								



T-Max® P insert for turning

S-style insert (Square)



B

	LE		S	RE	GB	BN	ISO CODE	K			H			ANSI CODE
	7525	7015						7025	7525	7015	7025	7525		
Finishing	09	3/8	2.2	3.18	0.8	30°	0.10	SNGA090308S01030A					★	SNGA322S0330A
			.087	.125	.031	30°	.004							
	12	1/2	2.8	4.76	0.8	30°	0.10	SNGA120408S01030A			☆	★		SNGA432S0330A
			.110	.188	.031	30°	.004							
			2.8	4.76	0.8	20°	0.10	SNGA120408T01020B	★				★	SNGA432T0320B
			.110	.188	.031	20°	.004							
			2.8	4.76	1.2	30°	0.10	SNGA120412S01030A			☆	★		SNGA433S0330A
			.110	.188	.047	30°	.004							
			2.8	4.76	1.2	35°	0.20	SNGA120412S02035A					★	SNGA433S0835A
			.110	.188	.047	35°	.008							
			2.8	4.76	1.2	35°	0.20	SNGA120412S02035B					★	SNGA433S0835B
			.110	.188	.047	35°	.008							
		2.8	4.76	1.2	20°	0.10	SNGA120412T01020B	★				★	SNGA433T0320B	
		.110	.188	.047	20°	.004								



C

D



T-Max® P insert for turning

T-style insert (Triangular)



	LE		S	RE	GB	BN	ISO CODE	H		ANSI CODE	
	7125	7135						CB20			
Finishing	16	3/8	2.5	4.76	0.8	30°	0.15	TNGA160408S01530F	★		TNGA332S0530F
			.098	.188	.031	30°	.006				
			3.1	4.76	1.2	25°	0.10	TNGA160412S01025F	★		TNGA333S0325F
			.122	.188	.047	25°	.004				
			3.1	4.76	1.2	30°	0.15	TNGA160412S01530F	★		TNGA333S0530F
			.122	.188	.047	30°	.006				
			2.8	4.76	1.6	25°	0.10	TNGA160416S01025F	★	☆	TNGA334S0325F
			.110	.188	.063	25°	.004				
			3.9	4.76	2.0	25°	0.10	TNGA160420S01025F	★	☆	TNGA335S0325F
			.154	.188	.079	25°	.004				
			3.6	4.76	2.4	25°	0.10	TNGA160424S01025F	★	☆	TNGA336S0325F
			.142	.188	.094	25°	.004				
			3.6	4.76	0.4	20°	0.10	TNMA160404S01020E		☆	TNMA331S0320E
			.142	.188	.016	20°	.004				
			3.3	4.76	0.8	20°	0.10	TNMA160408S01020E		☆	TNMA332S0320E
		.130	.188	.031	20°	.004					
	22	1/2	3.2	4.76	0.8	20°	0.10	TNMA220408S01020E		☆	TNMA432S0320E
		.126	.188	.031	20°	.004					
		2.9	4.76	1.2	20°	0.10	TNMA220412S01020E		☆	TNMA433S0320E	
		.114	.188	.047	20°	.004					



D2



D3





D6



T-Max® P insert for turning

T-style insert (Triangular)




	LE	S	RE	GB	BN	ISO CODE	K					H					ANSI CODE
							7525	7015	7025	7105	7115	7525	7015	7025	7105	7115	
Finishing	11	1/4	1.8	3.18	0.4	30°	0.10	TNGA110304S01030A		☆	★					TNGA221S0330A	
			.071	.125	.016	30°	.004										
			1.8	3.18	0.4	20°	0.10	TNGA110304T01020B	★						★	TNGA221T0320B	
			.071	.125	.016	20°	.004										
			1.5	3.18	0.8	30°	0.10	TNGA110308S01030A		☆	★					TNGA222S0330A	
			.059	.125	.031	30°	.004										
			2.1	3.18	0.8	20°	0.10	TNGA110308T01020B	★						★	TNGA222T0320B	
			.083	.125	.031	20°	.004										
		16	3/8	3.0	4.76	0.4	30°	0.10	TNGA160404S01030A		☆	★				TNGA331S0330A	
				.118	.188	.016	30°	.004									
				2.8	4.76	0.4	25°	0.15	TNGA160404S01525H				☆	★		TNGA331S0525H	
				.110	.188	.016	25°	.006									
			1.8	4.76	0.4	20°	0.10	TNGA160404T01020B	★					★	TNGA331T0320B		
			.071	.188	.016	20°	.004										
			2.7	4.76	0.8	30°	0.10	TNGA160408S01030A		☆	★				TNGA332S0330A		
			.106	.188	.031	30°	.004										
			2.5	4.76	0.8	25°	0.15	TNGA160408S01525H				☆	★		TNGA332S0525H		
			.098	.188	.031	25°	.006										
			2.8	4.76	0.8	30°	0.15	TNGA160408S01530B						★	TNGA332S0630B		
			.110	.188	.031	30°	.006										
			2.0	4.76	0.8	35°	0.20	TNGA160408S02035A				★			TNGA332S0835A		
			.079	.188	.031	35°	.008										
			2.8	4.76	0.8	35°	0.20	TNGA160408S02035B						★	TNGA332S0835B		
			.110	.188	.031	35°	.008										
			2.8	4.76	0.8	20°	0.10	TNGA160408T01020B	★					★	TNGA332T0320B		
			.110	.188	.031	20°	.004										
			2.4	4.76	1.2	30°	0.10	TNGA160412S01030A		☆	★				TNGA333S0330A		
			.094	.188	.047	30°	.004										
			2.2	4.76	1.2	25°	0.15	TNGA160412S01525H				☆	★		TNGA333S0525H		
			.087	.188	.047	25°	.006										
			2.4	4.76	1.2	35°	0.20	TNGA160412S02035A				★			TNGA333S0835A		
			.094	.188	.047	35°	.008										
			2.4	4.76	1.2	20°	0.10	TNGA160412T01020B	★					★	TNGA333T0320B		
			.094	.188	.047	20°	.004										




T-Max® P insert for turning

V-style insert (Rhombic 35°)




	LE	S	RE	GB	BN	ISO CODE	H				ANSI CODE			
							7015	7025	7105	7115		7125		
Finishing	16	3/8	2.1	4.76	0.4	20°	0.10	VNGA160404S01020A	★				VNGA331S0320A	
			.083	.188	.016	20°	.004							
			4.4	4.76	0.4	30°	0.10	VNGA160404S01030A	☆	★			VNGA331S0330A	
			.173	.188	.016	30°	.004							
			2.5	4.76	0.4	25°	0.15	VNGA160404S01525H			☆	★	★	VNGA331S0525H
			.098	.188	.016	25°	.006							
			2.4	4.76	0.8	20°	0.10	VNGA160408S01020A		★				VNGA332S0320A
			.094	.188	.031	20°	.004							
			3.5	4.76	0.8	30°	0.10	VNGA160408S01030A	☆	★				VNGA332S0330A
			.138	.188	.031	30°	.004							
			2.5	4.76	0.8	25°	0.15	VNGA160408S01525H			☆	★	★	VNGA332S0525H
			.098	.188	.031	25°	.006							
			2.4	4.76	0.8	35°	0.20	VNGA160408S02035A	☆	★				VNGA332S0835A
			.094	.188	.031	35°	.008							



T-Max® P insert for turning

W-style insert (Trigon 80°)



	LE	S	RE	BS	GB	BN	ISO CODE	K						H						ANSI CODE
								7525	7015	7025	7105	7115	7125	7135	7525	7015	7025	7105	7115	
B	06	3/8	2.4	4.76	0.4	30°	0.10	WNGA060404S01030A		☆	★							WNGA331S0330A		
			.094	.188	.016	30°	.004													
			2.6	4.76	0.4	25°	0.15	WNGA060404S01525H				☆	★					WNGA331S0525H		
			.102	.188	.016	25°	.006													
			1.8	4.76	0.4	20°	0.10	WNGA060404T01020B	★								★	WNGA331T0320B		
			.071	.188	.016	20°	.004													
			2.4	4.76	0.8	30°	0.10	WNGA060408S01030A		☆	★							WNGA332S0330A		
			.094	.188	.031	30°	.004													
			2.5	4.76	0.8	25°	0.15	WNGA060408S01525H				☆	★					WNGA332S0525H		
			.098	.188	.031	25°	.006													
			2.4	4.76	0.8	20°	0.10	WNGA060408T01020B	★								★	WNGA332T0320B		
			.094	.188	.031	20°	.004													
			1.8	4.76	0.4	0.8	20°	0.10	WNGA060404T01020BWG	★								★	WNGA331T0320BWG	
			.071	.188	.016	.031	20°	.004												
			2.4	4.76	0.8	1.0	20°	0.10	WNGA060408T01020BWG	★								★	WNGA332T0320BWG	
			.094	.188	.031	.039	20°	.004												
			2.4	4.76	0.4	0.5	30°	0.10	WNGA060404S01030AWH			★						WNGA331S0330AWH		
			.094	.188	.016	.018	30°	.004												
			2.6	4.76	0.4	0.5	20°	0.15	WNGA060404S01520HWH				☆	★				WNGA331S0520HWH		
			.102	.188	.016	.018	20°	.006												
		2.4	4.76	0.4	0.5	30°	0.10	WNGA060404T01030AWH		★							WNGA331T0330AWH			
		.094	.188	.016	.018	30°	.004													
		2.4	4.76	0.8	0.6	30°	0.10	WNGA060408S01030AWH			★						WNGA332S0330AWH			
		.094	.188	.031	.022	30°	.004													
		2.5	4.76	0.8	0.6	20°	0.15	WNGA060408S01520HWH				☆	★				WNGA332S0520HWH			
		.098	.188	.031	.022	20°	.006													
		2.4	4.76	0.8	0.6	30°	0.10	WNGA060408T01030AWH	★								WNGA332T0330AWH			
		.094	.188	.031	.022	30°	.004													
C	Finishing	08	1/2	3.0	4.76	0.4	30°	0.10	WNGA080404S01030A		☆	★						WNGA431S0330A		
				.118	.188	.016	30°	.004												
				2.6	4.76	0.4	25°	0.15	WNGA080404S01525H				☆	★				WNGA431S0525H		
				.102	.188	.016	25°	.006												
				3.1	4.76	0.4	20°	0.10	WNGA080404T01020B	★								★	WNGA431T0320B	
				.122	.188	.016	20°	.004												
				2.9	4.76	0.8	30°	0.10	WNGA080408S01030A		☆	★							WNGA432S0330A	
				.114	.188	.031	30°	.004												
				2.5	4.76	0.8	25°	0.15	WNGA080408S01525H				☆	★	★				WNGA432S0525H	
				.098	.188	.031	25°	.006												
				2.5	4.76	0.8	30°	0.15	WNGA080408S01530F									★	WNGA332S0530F	
				.098	.188	.031	30°	.006												
				2.0	4.76	0.8	35°	0.20	WNGA080408S02035A		☆	★							WNGA432S0835A	
				.079	.188	.031	35°	.008												
				3.0	4.76	0.8	20°	0.10	WNGA080408T01020B	★									★	WNGA432T0320B
				.118	.188	.031	20°	.004												
				2.8	4.76	1.2	30°	0.10	WNGA080412S01030A		☆	★							WNGA433S0330A	
				.110	.188	.047	30°	.004												
				2.4	4.76	1.2	25°	0.15	WNGA080412S01525H				☆	★	★				WNGA433S0525H	
				.095	.188	.047	25°	.006												
		2.9	4.76	1.2	30°	0.15	WNGA080412S01530F										★	WNGA333S0530F		
		.113	.188	.047	30°	.006														
		2.9	4.76	1.2	20°	0.10	WNGA080412T01020B	★									★	WNGA433T0320B		
		.114	.188	.047	20°	.004														
		3.1	4.76	0.4	0.8	20°	0.10	WNGA080404T01020BWG	★								★	WNGA431T0320BWG		
		.122	.188	.016	.031	20°	.004													
		3.0	4.76	0.8	1.0	20°	0.10	WNGA080408T01020BWG	★									★	WNGA432T0320BWG	
		.118	.188	.031	.039	20°	.004													
		3.0	4.76	0.4	0.5	30°	0.10	WNGA080404S01030AWH			★							WNGA431S0330AWH		
		.118	.188	.016	.018	30°	.004													
		2.6	4.76	0.4	0.5	20°	0.15	WNGA080404S01520HWH				☆	★					WNGA431S0520HWH		
		.102	.188	.016	.018	20°	.006													



D2





D3



D6

T-Max® P insert for turning

W-style insert (Trigon 80°)



	MIC		LE	S	RE	BS	GB	BN	ISO CODE	K						ANSI CODE	
	08	1/2								7525	7015	7025	7105	7115	7125		7135
Finishing	.118	.188	.016	.018	30°	.004			WNGA080404T01030AWH	*							WNGA431T0330AWH
	2.9	4.76	0.8	0.6	30°	0.10			WNGA080408S01030AWH		*						WNGA432S0330AWH
	.114	.188	.031	.022	30°	.004			WNGA080408S01520HWH			*	*				WNGA432S0520HWH
	2.5	4.76	0.8	0.6	20°	0.15			WNGA080408T01030AWH	*							WNGA432T0330AWH
	.098	.188	.031	.022	20°	.006			WNGA080408T01030AWH		*						WNGA433S0330AWH
	2.9	4.76	0.8	0.6	30°	0.10			WNGA080412S01030AWH			*					WNGA433S0520HWH
	.114	.188	.031	.022	30°	.004			WNGA080412S01520HWH			*	*				WNGA433T0330AWH
	2.8	4.76	1.2	0.6	30°	0.10			WNGA080412S01520HWH				*				WNGA433T0520HWH
	.110	.188	.047	.024	30°	.004			WNGA080412T01030AWH					*			WNGA433T0330AWH
	2.4	4.76	1.2	0.6	20°	0.15			WNGA080412T01030AWH	*							WNGA433T0520HWH
	.095	.188	.047	.024	20°	.006			WNGA080412T01030AWH		*						WNGA433T0330AWH
	2.8	4.76	1.2	0.6	30°	0.10			WNGA080412T01030AWH			*					WNGA433T0330AWH
.110	.188	.047	.024	30°	.004			WNGA080412T01030AWH				*				WNGA433T0330AWH	

B

C

D



D2



D3



D6



T-Max®


For productive turning of difficult to machine materials

Application

- Longitudinal turning
- Face turning
- Profiling
- Roughing to finishing

Benefits and features

- Reliable and secure machining, even in roughing applications
- Double sided inserts with strong edges
- Secure and rigid-clamping and top clamp



Clamping

- Rigid clamp and top clamp

Tools

- Coromant Capto® cutting units
- Shank tools

Inserts



- T-Max inserts, without holes.



A31

T-Max® insert for turning

C-style insert (Rhombic 80°)



Finishing	IC		LE	S	RE	GB	BN	ISO CODE	K 7925	ANSI CODE
	12	1/2								
	.460	.188	11.7	4.76	1.2	20°	0.25	CNGN120412S02520M	★	CNG433S0820M
	.445	.188	11.3	4.76	1.6	20°	0.25	CNGN120416S02520M	★	CNG434S0820M



D2




D3



D6

T-Max® insert for turning

R-style insert (Round)



ENG

B

			S	RE	GB	BN	ISO CODE	K			H			ANSI CODE
	7925	CB50						CB60	7925	CB50	CB60			
Finishing	06	1/4	3.18	3.0	20°	0.25	RNGN060300S02520M	*						RNG22S1020M
			.125	.118	20°	.010								
	09	3/8	3.18	4.8	20°	0.25	RNGN090300S02520M	*						RNG32S1020M
			.125	.188	20°	.010								
	12	1/2	3.18	6.4	20°	0.25	RNGN120300S02520M	*						RNG42S1020M
			.125	.250	20°	.010								
		4.76	6.4	20°	0.25	RNGN120400S02520M	*							RNG43S1020M
		.188	.250	20°	.010									
		4.76	6.4				RNGN120400FD	☆	☆					RNG43FD
		.188	.250											

C

D



D2




D3



D6

T-Max® insert for turning

S-style insert (Square)



	LE	S	RE	GB	BN	ISO CODE	K		H		ANSI CODE
							7925	CB50	CB50	CB50	
Finishing	09	3/8	8.3	3.18	1.2	20°	0.25	SNGN090312S02520M	★		SNG323S1020M
			.328	.125	.047	20°	.010				
	12	1/2	11.5	4.76	1.2	20°	0.25	SNGN120412S02520M	★		SNG433S1020M
			.453	.188	.047	20°	.010				
			11.1	4.76	1.6	20°	0.25	SNGN120416S02520M	★		SNG434S1020M
			.437	.188	.063	20°	.010				
			11.9	4.76	0.8			SNGN120408FD	☆	☆	SNG432FD
			.469	.188	.031						
			11.5	4.76	1.2			SNGN120412FD	☆	☆	SNG433FD
			.453	.188	.047						
		11.1	4.76	1.6			SNGN120416FD	☆	☆	SNG434FD	
		.437	.188	.063							



CoroTurn® XS

Internal turning, face grooving and threading of small components

Application

- Internal turning
- Copying
- Backboring
- Profiling
- Grooving
- Face grooving
- Pre-parting
- Threading




Benefits and features

- Optimized for machining of small high quality features
- High precision and repeatability
- Reliable and easy-to-use clamping system
- Precision ground tools for high repeatability
- Longer tool life by minimized micro vibrations with cylindrical carbide shank adaptors
- Clamping nut ensures easy change of cutting tool with cylindrical carbide shank adaptors

www.sandvik.coromant.com/coroturnxs


Internal coolant

- The adaptors are designed with internal precision coolant supply.
- Selectable coolant direction for better chip evacuation and safe machining




Locking precision

Precise location into the boring bar due to a locating pin.



CoroTurn® XS solid carbide tool for turning



CZC _{MS}	DMIN ₁	LU	RE	APMX	RMPX	OHX	Ordering code	H	Dimensions, mm, inch			
									7015	DCON _{MS}	WB	LF
4	1.7	6.0	0.100	0.20	17°	13.0	CXS-04T098-10-1706R	★	4	1.1	27.3	0.7
	.067	.236	.004	.008	.512				.157	.041	1.073	.028
4	2.2	9.0	0.100	0.20	17°	13.0	CXS-04T098-10-2209R	★	4	1.6	27.3	1.0
	.087	.354	.004	.008	.512				.157	.061	1.073	.037
4	2.7	10.0	0.150	0.20	17°	13.0	CXS-04T098-15-2710R	★	4	2.1	27.3	1.2
	.106	.394	.006	.008	.512				.157	.081	1.073	.047
4	3.2	15.0	0.150	0.20	17°	18.0	CXS-04T098-15-3215R	★	4	2.6	32.3	1.5
	.126	.591	.006	.008	.709				.157	.100	1.270	.057
4	3.7	15.0	0.150	0.20	17°	18.0	CXS-04T098-15-3715R	★	4	3.1	32.3	1.7
	.146	.591	.006	.008	.709				.157	.120	1.270	.067
4	4.2	10.0	0.150	0.30	17°	13.0	CXS-04T098-15-4210R	★	4	3.5	27.3	2.0
	.165	.394	.006	.012	.512				.157	.136	1.073	.077
4	4.2	15.0	0.150	0.30	17°	18.0	CXS-04T098-15-4215R	★	4	3.5	32.3	2.0
	.165	.591	.006	.012	.709				.157	.136	1.270	.077
4	4.2	20.0	0.150	0.30	17°	23.0	CXS-04T098-15-4220R	★	4	3.5	37.3	2.0
	.165	.787	.006	.012	.906				.157	.136	1.467	.077
4	4.2	25.0	0.150	0.30	17°	28.0	CXS-04T098-15-4225R	★	4	3.5	42.3	2.0
	.165	.984	.006	.012	1.102				.157	.136	1.663	.077
5	5.2	10.0	0.200	0.50	17°	13.0	CXS-05T098-20-5210R	★	5	4.3	32.3	2.5
	.205	.394	.008	.020	.512				.197	.167	1.270	.096
5	5.2	20.0	0.200	0.50	17°	23.0	CXS-05T098-20-5220R	★	5	4.3	42.3	2.5
	.205	.787	.008	.020	.906				.197	.167	1.663	.096
5	5.2	25.0	0.200	0.50	17°	28.0	CXS-05T098-20-5225R	★	5	4.3	47.3	2.5
	.205	.984	.008	.020	1.102				.197	.167	1.860	.096
5	5.2	30.0	0.200	0.50	17°	33.0	CXS-05T098-20-5230R	★	5	4.3	52.3	2.5
	.205	1.181	.008	.020	1.299				.197	.167	2.057	.096
6	6.2	15.0	0.200	0.50	17°	18.0	CXS-06T098-20-6215R	★	6	5.3	37.3	3.0
	.244	.591	.008	.020	.709				.236	.207	1.467	.116
6	6.2	20.0	0.200	0.50	17°	23.0	CXS-06T098-20-6220R	★	6	5.3	42.3	3.0
	.244	.787	.008	.020	.906				.236	.207	1.663	.116
6	6.2	25.0	0.200	0.50	17°	28.0	CXS-06T098-20-6225R	★	6	5.3	47.3	3.0
	.244	.984	.008	.020	1.102				.236	.207	1.860	.116
6	6.2	30.0	0.200	0.50	17°	33.0	CXS-06T098-20-6230R	★	6	5.3	52.3	3.0
	.244	1.181	.008	.020	1.299				.236	.207	2.057	.116
6	6.2	40.0	0.200	0.50	17°	43.0	CXS-06T098-20-6240R	★	6	5.3	62.3	3.0
	.244	1.575	.008	.020	1.693				.236	.207	2.451	.116
7	7.2	25.0	0.200	0.50	17°	28.0	CXS-07T098-20-7225R	★	7	6.3	47.3	3.5
	.283	.984	.008	.020	1.102				.276	.246	1.860	.136
7	7.2	30.0	0.200	0.50	17°	33.0	CXS-07T098-20-7230R	★	7	6.3	52.3	3.5
	.283	1.181	.008	.020	1.299				.276	.246	2.057	.136
7	7.2	40.0	0.200	0.50	17°	43.0	CXS-07T098-20-7240R	★	7	6.3	62.3	3.5
	.283	1.575	.008	.020	1.693				.276	.246	2.451	.136
7	7.2	50.0	0.200	0.50	17°	53.0	CXS-07T098-20-7250R	★	7	6.3	72.3	3.5
	.283	1.969	.008	.020	2.087				.276	.246	2.844	.136

CZC_{MS} to correspond with CZC_{WS} on adaptor.

R = Right hand, L = Left hand



D2



D8

Parting and grooving

CoroCut®1-2 B2

Inserts B3-B7

CoroTurn®XS B8

Cutting tools B9

CoroCut®MB B10

Cutting tools B11-B12

CoroCut® 1-2

Parting, profiling and grooving operations

Application

- Parting off
- External grooving
- Internal grooving
- Face grooving
- Profiling

B

Benefits and features

- Strong tool material alloy for high fatigue resistance
- Plug and play adaptors make it easy to connect the coolant
- Easy to change inserts: no torque wrench needed – always correct clamping with quick-release key



C

Note: In parting off and grooving CoroCut® 1-2 is the best choice to depths where the 2-edged inserts can be used.

www.sandvik.coromant.com/corocut1-2

Inserts

- Geometries and grades for all applications and feeds
- Insert grades in advanced cutting materials CBN
- Xcel inserts for excellent surface finish

Tools

- Coromant Capto® cutting units
- Shank tools
- QS™ shanks
- Parting blades
- Boring bars
- CoroTurn® SL heads


D

Rigid spring clamping

The system combines rigid spring clamping mechanism with railed insert seat and long inserts for exceptional stability.

Over- and under coolant

Tools with internal over- and under coolant available for best chip control and tool life.





B3



D3

CoroCut® 1-2 insert for grooving



CoroCut® 2-edge


					Ordering code	H	Dimensions, mm, inch					
	SSC	CW	REL	RER			CB20	AN	CWTOLL	CWTOLU	RETOLL	RETOLU
Finishing		G	3.00	0.20	0.20	N123G1-0300-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050
			.118	.008	.008							
			3.18	0.20	0.20	N123G1-0318-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050
			.125	.008	.008							
		H	4.00	0.20	0.20	N123H1-0400-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050
			.157	.008	.008							
		5.00	0.20	0.20	N123H1-0500-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050	
		.197	.008	.008								
	J	6.00	0.20	0.20	N123J1-0600-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050	
		.236	.008	.008								
	K	6.35	0.20	0.20	N123K1-0635-0002-GE	☆	7°	-0.020	0.020	-0.050	0.050	
		.250	.008	.008								

SSC = To correspond with SSC on holder.

N = Neutral



CoroCut® 1-2 insert for grooving



CoroCut® 1-edge

	SSC	CW	RE	REL	RER	Ordering code	S H		Dimensions, mm, inch						
							7015	7016	GB	BN	AN	CWTOLL	CWTOLU	RETOLL	RETOLU
							*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
Finishing	G	3.00		0.40	0.40	N123G1-030004S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.118		.016	.016				25°	.004		-.0008	.0008	-.0020	.0020
	H	4.00		0.40	0.40	N123H1-040004S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.157		.016	.016				25°	.004		-.0008	.0008	-.0020	.0020
		5.00		0.40	0.40	N123H1-050004S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.197		.016	.016				25°	.004		-.0008	.0008	-.0020	.0020
	J	6.00		0.40	0.40	N123J1-060004S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.236		.016	.016				25°	.004		-.0008	.0008	-.0020	.0020
	L	8.00	0.80	0.80	0.80	N123L1-080008S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.315	.031	.031	.031				25°	.004		-.0008	.0008	-.0020	.0020

SSC = To correspond with SSC on holder.

N = Neutral



D2




D3



D11

CoroCut® 1-2 insert for profiling



CoroCut® 1-edge



						S	H	Dimensions, mm, inch							
		SSC	CW	RE	APMX	Ordering code	7015	7015	GB	BN	AN	CWTOLL	CWTOLU	RETOLL	RETOLU
Finishing		F	3.00	1.50	2.5	N123F1-0300S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.020	0.020
			.118	.059	.098				25°	.004		-.0008	.0008	-.0008	.0008
		H	4.00	2.00	3.4	N123H1-0400S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.020	0.020
			.157	.079	.134				25°	.004		-.0008	.0008	-.0008	.0008
			5.00	2.50	4.5	N123H1-0500S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.020	0.020
			.197	.098	.177				25°	.004		-.0008	.0008	-.0008	.0008
		J	6.00	3.00	5.3	N123J1-0600S01025	*	*	25°	0.1	7°	-0.020	0.020	-0.020	0.020
			.236	.118	.209				25°	.004		-.0008	.0008	-.0008	.0008

SSC = To correspond with SSC on holder.

N = Neutral




CoroCut® 1-2 insert for profiling





B


CoroCut® 1-edge

	SSC	CW	RE	CDX	APMX	Ordering code	S H				Dimensions, mm, inch					
							S		H		AN	CWTOLL	CWTOLU	RETOLL	RETOLU	
							7015	7015	7025	CB20						
Finishing 	F	3.00	1.50	0.6	0.6	N123F1-0300-RE	★	★	☆	☆	7°	-0.020	0.020	-0.020	0.020	
		.118	.059	.024								-0.008	.008	-0.008	.008	
		3.18	1.59	0.6			N123F1-0318-RE	★	★			7°	-0.020	0.020	-0.020	0.020
		.125	.063	.024									-0.008	.008	-0.008	.008
	HN	2.00	1.00	5.0	0.5	0.5	N123H1-0200-RE	★	★	☆		7°	-0.020	0.020	-0.010	0.010
		.079	.039	.197	.020								-0.008	.008	-0.004	.004
	H	4.00	2.00	0.7			N123H1-0400-RE	★	★	☆	☆	7°	-0.020	0.020	-0.020	0.020
		.157	.079	.026									-0.008	.008	-0.008	.008
		5.00	2.50	0.7			N123H1-0500-RE	★	★	☆		7°	-0.020	0.020	-0.020	0.020
		.197	.098	.028									-0.008	.008	-0.008	.008
	J	6.00	3.00	0.8			N123J1-0600-RE	★	★	☆		7°	-0.020	0.020	-0.020	0.020
		.236	.118	.030									-0.008	.008	-0.008	.008
	6.35	3.18	0.8			N123J1-0635-RE	★	★			7°	-0.020	0.020	-0.020	0.020	
	.250	.125	.030									-0.008	.008	-0.008	.008	
L	8.00	4.00	0.9			N123L1-0800-RE	★	★	☆		7°	-0.020	0.020	-0.020	0.020	
	.315	.157	.033									-0.008	.008	-0.008	.008	

C



CoroCut® 1-edge

	SSC	CW	RE	CDX	APMX	Ordering code	S H		Dimensions, mm, inch						
							S	H	AN	CWTOLL	CWTOLU	RETOLL	RETOLU		
							7015	7015							
Finishing 	HL	2.00	1.00	5.0	0.5	L123H1-0200-RE	★	★	7°	-0.020	0.020	-0.010	0.010		
		.079	.039	.197	.020							-0.008	.008	-0.004	.004
	HR	2.00	1.00	5.0	0.5	R123H1-0200-RE	★	★	7°	-0.020	0.020	-0.010	0.010		
		.079	.039	.197	.020							-0.008	.008	-0.004	.004

SSC = To correspond with SSC on holder.

N = Neutral, R = Right hand, L = Left hand



D2




D3



D11

CoroCut® 1-2 insert for turning



CoroCut® 1-edge

		H		Dimensions, mm, inch													
		7/105	7/115	GB	BN	AN	CWTOLL	CWTOLU	RETOLL	RETOLU							
Finishing	G	3.00	1.60	1.60	0.40	0.40	0.12	N123G1-0300S01025-XB	★	★	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.118	.063	.063	.016	.016	.005				25°	.004		-.0008	.0008	-.0020	.0020
	J	5.00	2.60	2.60	0.20	0.20		N123J1-0500S01025-XB	☆	★	25°	0.1	7°	-0.020	0.020	-0.050	0.050
		.197	.102	.102	.008	.008					25°	.004		-.0008	.0008	-.0020	.0020

SSC = To correspond with SSC on holder.

N = Neutral



CoroTurn® XS

Internal turning, face grooving and threading of small components

Application

- Internal turning
- Copying
- Backboring
- Profiling
- Grooving
- Face grooving
- Pre-parting
- Threading



Benefits and features

- Optimized for machining of small high quality features
- High precision and repeatability
- Reliable and easy-to-use clamping system
- Precision ground tools for high repeatability
- Longer tool life by minimized micro vibrations with cylindrical carbide shank adaptors
- Clamping nut ensures easy change of cutting tool with cylindrical carbide shank adaptors

www.sandvik.coromant.com/coroturnxs


Internal coolant

- The adaptors are designed with internal precision coolant supply.
- Selectable coolant direction for better chip evacuation and safe machining




Locking precision

Precise location into the boring bar due to a locating pin.



CoroTurn® XS solid carbide tool for grooving



											H	Dimensions, mm, inch							
											7015	DCON _{MS}	WB	LF	WF	CWTOLL	CWTOLU		
	CZC _{MS}	CW	KCHL	KCHR	CHWL	CHWR	CDX	DMIN ₁	LU	OHX	Ordering code	★							
	6	1.00	45°	45°	0.04	0.04	1.8	6.2	15.0	18.0	CXS-06G100-6215R		6	4.0	37.3	3.0	0.000	0.050	
					.002	.002	.071	.244	.591	.709				.236	.156	1.467	.116	.0000	.0020
	6	1.50	45°	45°	0.04	0.04	1.8	6.2	15.0	18.0	CXS-06G150-6215R	★	6	4.0	37.3	3.0	0.000	0.050	
					.002	.002	.071	.244	.591	.709									



CoroCut® MB

For internal machining with high precision

Application

- For internal machining of small holes
- Pre-parting
- Grooving
- Face grooving
- Profiling
- Turning
- Copying
- Back boring
- Threading

Benefits and features

- Vibration free machining
- Fast set up for both tool and insert
- Stable high precision interface between interface and tool holder
- Front-mounted exchangeable cutting tool
- Sharp cutting edges
- Geometries and grades for all materials
- Carbide shanks for long overhangs
- Through coolant
- Easy fix clamping
- Grooving tools in a large variety of widths and corner radii – also for standardized grooves such as O-rings and circlip grooves.



www.sandvik.coromant.com/corocutmb


EasyFix

Cylindrical steel and carbide boring bars to be used with EasyFix sleeves for exact centre height.

CoroCut® MB boring bars

For stability and accessibility the bars are designed with an eccentric head with oval cross section.

CoroCut® MB solid carbide head for grooving




		H Dimensions, mm, inch												
CZC _{MS}	CW	KCHL	KCHR	CHWL	CHWR	CDX	DMIN ₁	Ordering code	H	DCON _{MS}	LF	WF	CWTOLL	CWTOLU
07	1.00 .039	45°	45°	0.04 .002	0.04 .002	2.8 .110	11.0 .433	MB-07G100-00-11R	★	7 .276	3.9 .154	6.8 .268	0.000 .0000	0.050 .0020
07	1.50 .059	45°	45°	0.04 .002	0.04 .002	2.8 .110	11.0 .433	MB-07G150-00-11R	★	7 .276	3.9 .154	6.8 .268	0.000 .0000	0.050 .0020

CZC_{MS} to correspond with CZC_{WS} on adaptor.






D2



D10



CoroCut® MB solid carbide head for turning



						H	Dimensions, mm, inch		
CZC _{MS}	RE	DMIN ₁	APMX	RMPX	Ordering code	7015	DCON _{MS}	LF	WF
07	0.20	10.0	1.8	15°	MB-07T093-02-10R	★	7	3.9	5.6
	.008	.394	.071				.276	.154	.220

CZC_{MS} to correspond with CZC_{WS} on adaptor.



D2



D10

Thread turning

CoroThread® 266

C2

Inserts

C3

CoroTurn® XS

C4

Cutting tools

C5

CoroCut® MB

C6

Cutting tools

C7

CoroThread® 266

Ultra-rigid thread turning for all types of threads

Application

- External threads
- Internal threads

Benefits and features


- Reduced machine- and downtime
- Excellent surface finish due to the exceptional stability
- Three sharp cutting edges for high-quality threads
- Multi-point inserts available, require fewer passes resulting in increased productivity
- Large standard product range of tools and thread profile inserts
- Unique guide rail interface between the insert and tip seat
- Good edge indexing
- Easy to mount the insert correctly




www.sandvik.coromant.com/corothread266

Inserts


- Insert geometries and grades for all materials
- Tailor Made inserts for almost any thread form or pitch



Standard
A-geometry



Sharp
F-geometry



Chip-breaking
C-geometry

Tools


- Coromant Capto® cutting units
- Shank tools
- Boring bars
- CoroTurn® SL heads



Three different threading insert types


Full profile

High productivity




V-profile

Minimum tool
inventory



Multi-point

Economical mass
production



Secure iLock™ clamping

The slotted insert sits rigidly on the T-rails in the pocket eliminating any insert movement caused by cutting force variations.




C3



D3

CoroThread® 266 insert for thread turning

V-profile 60° Non-topping



External right-hand threads

							H	Dimensions, mm, inch						
							7015	RER	REL	HA	HB	PDX	PDY	
		TPN	TPX	TPIN	TPIX	NT	Ordering code	★	0.13	0.13	1.68	0.14	1.00	1.03
16	3/8	1.0	2.0	12.0	24.0	1	266RG-16VM01A001EE	★	.005	.005	.0661	.0055	.039	.041
		1.5	3.0	8.0	16.0	1	266RG-16VM01A002EE	★	0.20	0.20	2.64	0.20	1.50	1.03
									.008	.008	.1039	.0079	.059	.041

External left-hand threads

							H	Dimensions, mm, inch						
							7015	RER	REL	HA	HB	PDX	PDY	
		TPN	TPX	TPIN	TPIX	NT	Ordering code	★	0.09	0.09	2.54	0.09	1.50	1.01
16	3/8	1.5	3.0	8.0	16.0	1	266RL-16VM01A002EE	★	.004	.004	.1000	.0035	.059	.040

R = Right hand, L = Left hand



D2



D3

CoroTurn® XS

Internal turning, face grooving and threading of small components

B **Application**

- Internal turning
- Copying
- Backboring
- Profiling
- Grooving
- Face grooving
- Pre-parting
- Threading



Benefits and features


- Optimized for machining of small high quality features
- High precision and repeatability
- Reliable and easy-to-use clamping system
- Precision ground tools for high repeatability
- Longer tool life by minimized micro vibrations with cylindrical carbide shank adaptors
- Clamping nut ensures easy change of cutting tool with cylindrical carbide shank adaptors

C

www.sandvik.coromant.com/coroturnxs


Internal coolant

- The adaptors are designed with internal precision coolant supply.
- Selectable coolant direction for better chip evacuation and safe machining



Locking precision



Precise location into the boring bar due to a locating pin.



D


CoroTurn® XS solid carbide tool for thread turning

V-profile 60° Non-topping



Internal right-hand threads

CZC _{MS}	TPN	TPX	TPIN	TPIX	DMIN ₁	LU	OHX	Ordering code	H Dimensions, mm, inch								
									DCON _{MS}	WB	CF	LPR	LF	WF	HA	HB	
6	1.00	1.25	20.0	24.0	6.2	15.0	17.5	CXS-06TH100VM-6215R	★	6	3.6	0.1	37.9	37.3	3.0	0.8	0.1
	.039	.049			.244	.591	.687			.236	.140	.005	1.490	1.469	.116	.031	.004
6	1.50	1.75	16.0	18.0	6.2	15.0	17.2	CXS-06TH150VM-6215R	★	6	3.6	0.2	38.3	37.3	3.0	1.1	0.2
	.059	.069			.244	.591	.676			.236	.140	.007	1.507	1.469	.116	.045	.006



CZC_{MS} to correspond with CZC_{WS} on adaptor.

R = Right hand, L = Left hand



CoroCut® MB

For internal machining with high precision

Application

- For internal machining of small holes
- Pre-parting
- Grooving
- Face grooving
- Profiling
- Turning
- Copying
- Back boring
- Threading

Benefits and features

- Vibration free machining
- Fast set up for both tool and insert
- Stable high precision interface between interface and tool holder
- Front-mounted exchangeable cutting tool
- Sharp cutting edges
- Geometries and grades for all materials
- Carbide shanks for long overhangs
- Through coolant
- Easy fix clamping
- Grooving tools in a large variety of widths and corner radii – also for standardized grooves such as O-rings and circlip grooves.



www.sandvik.coromant.com/corocutmb

EasyFix

Cylindrical steel and carbide boring bars to be used with EasyFix sleeves for exact centre height.




CoroCut® MB boring bars

For stability and accessibility the bars are designed with an eccentric head with oval cross section.

CoroCut® MB solid carbide head for thread turning

Metric 60° Full form

TCTR IT 6




Internal right-hand threads

						H Dimensions, mm, inch							
		CZC _{MS}	TP	DMIN ₁	Ordering code	7015	DCON _{MS}	CF	LPR	LF	WF	HA	HB
	07	1.0	10.0	MB-07TH100MM-10R	★	7	0.1	3.8	3.2	5.8	0.9	0.1	
		.039	.394				.276	.005	.150	.126	.228	.035	.004
	07	1.5	10.0	MB-07TH150MM-10R	★	7	0.2	3.8	3.0	5.8	1.4	0.2	
		.059	.394				.276	.007	.150	.118	.228	.054	.006

CZC_{MS} to correspond with CZC_{WS} on adaptor.

R = Right hand, L = Left hand





SANDVIK
Coromant

7125

General information

ISO 13399	D2
Tailor Made	D3
Safety information	D4
Coromant Recycling Concept (CRC)	D5
Code keys	D6
Alphanumeric index	D12

To make life easier, a new standard has been developed

ISO 13399 is an international standard that will simplify the exchange of data for cutting tools. You will notice a slight difference through the new parameters and descriptions of each tool.

For the first time ever, there is a standardized way of describing product data regarding cutting tools. When all tools in the industry share the same parameters and definitions, communicating tool information becomes very straightforward.

What does this mean to you?

Basically, it means that your systems can talk to ours, as they all speak the same language. Download product data from our web site and use it directly in your CAD/CAM software to assemble tools that you use in production. No need to look for information in catalogues and interpret data from one system to another. Imagine how much time this will save you!

Parameters in Hard Part Turning

Short name	Preferred Name
ANN	Clearance angle minor
APMX	Depth of cut maximum
BN	Face land width
CDX	Cutting depth maximum
CF	Spot chamfer
CW	Cutting width
CWTOLL	Cutting width lower tolerance
CWTOLU	Cutting width upper tolerance
CZC MS	Connection size code machine side
D1	Fixing hole diameter
DMIN	Minimum bore diameter
DMM	Shank diameter
GB	Face land angle
HA	Thread height theoretical
HB	Thread height difference
IC	Inscribed circle diameter
KAPR	Tool cutting edge angle
L	Cutting edge length
LE	Cutting edge effective length
LF	Functional length
LLTOLL	Length tolerance lower
LLTOLU	Length tolerance upper
LPR	Protruding length
LU	Usable length (max. recommended)
OHX	Overhang maximum
RE	Corner radius
REEQ	Corner radius equivalent
RETOLL	Corner radius lower tolerance
RETOLU	Corner radius upper tolerance
S	Insert thickness
SSC	Insert seat size code
TP	Thread pitch
TPIN	Threads per inch minimum
TPIX	Threads per inch maximum
TPN	Thread pitch minimum
TPX	Maximum thread pitch
TSYC	Tool style code
WB	Body width
WF	Functional width
WSC	Clamping width
WT	Weight of item
W1	Insert width

Tailor Made

Additional tool options designed for your specific requirements.



Apart from a comprehensive standard programme we can offer tools to your dimensions on standard tool terms. In our Tailor Made offer you are free to specify your own dimensions without paying the price of a special tool.

Customer		Customer No. (Coromant Internal)		Date
Street		Telephone		Customer attention
Post Code/City/State		Telefax		Issuer
Quantity		Customer denomination		

Inquiry/ordering No. _____

main catalogue or supplement catalogue
metric std Your value/ Your choice

above standard

14 Delivered with shims (with exceptions)
38, 1-254

essential pitch not valid for every combination
on insert size, outer diameter and pitch

Coromant Capto	HSK A
Size	Size
16 19.05-25.4 08	40 20-40 08/14
20 19.05-30.8 08/14	
25 25 08 08/14	
32 31.75-40 08/14	

HSK A	TDC
Size	Size
40 19.05-25 14	40 180-200 14
45 19.05-30 14	45 200-254 14
50 19.05-35 14	
55 19.05-40 14	

Coromant Capto	HSK A	Arbor mounting	TDC
Size	Size	Size	Size
16-25 50-80	30-35 40-80	40-60 60-63 65-69	40
30			

Insert size 14
L_{max} 38, 1-254
L_{min} 40-3 + D₂
D₂ =

size 50.8
If no value/choice is specified, it will be recommended by the system.

Even more possibilities thanks to tailored design!
If you do not find what you need in our comprehensive standard programme, choose the tool shape you require and we will tailor it for you to your dimensions.

- Quick quotation
- Easy to order
- Competitive delivery

CoroMill® 490

Standard insert, 490 08 14, 490 14 14, ...

Size	D ₂ (mm)	IC	Size	D ₂ (mm)	IC	Size	D ₂ (mm)	IC	Size	D ₂ (mm)	IC
16	19.05-25.4	08	16	19.05-25.4	08	C3	19.05-25	08/14	K3	20-40	08/14
20	19.05-30.8	08/14	20	19.05-30.8	08/14	C5	19.05-30	08/14			
25	25 08	08/14	25	25 08	08/14	C6	19.05-40	08/14			
32	31.75-40	08/14	32	31.75-40	08/14	C8	19.05-40	08/14			

Arbor mounting: TDA, TDB, TDC

Size	D ₂ (mm)	IC	Size	D ₂ (mm)	IC	Size	D ₂ (mm)	IC
16	37.5-50	08	32	100-125	14	40	180-200	14
20	38.1-80	08/14	38.1	125-180	14	47.825	200-254	14
22.225	38.1-80	08	40	125-180	14	60	200-254	14
25.4	40-100	08/14	50.8	180-200	14			
27	44-100	08/14						
31.75	100-125	14						

Options

Insert size 08 or 14 D ₂ -03, Diameter - 19.05-84 mm -14, Diameter - 38.1-254 mm	A ₂ Reach length, -08, 21 mm - 3 + D ₂ -14, 40 mm - 3 + D ₂
Pitch type Even or Differential P ₂ -03, No. of inserts 2-10 -14, No. of inserts 2-20	Total length, -03, 74-250 mm -14, 88-250 mm
Mounting Cylindrical, Weldon, Coromant Capto, HSK/A, Arbor mounting	Programming length, -08, 40-175.5 mm -14, 40-168.5 mm
d _{min} /D _{min} Mounting size, see above	Cooldown hole -09, Yes - D ₂ + 0.8 mm/No -14, Yes/No - all TDC and TDB size 50.8

Note: For specific details regarding the options, contact your Coromant sales representative.

What you can expect from us

- Quick quotation
- Easy ordering
- Performance guarantee at given product and cutting data
- Competitive delivery times

The Tailor Made option is available in the following product families:

Inserts - carbide

- CoroCut® 1-2
- CoroCut® QD
- CoroCut® 3
- T-Max® Q-Cut
- CoroThread® 266
- T-Max® U-Lock

Inserts - CBN

- T-Max® P
- T-Max®
- CoroTurn® 107
- CoroTurn® 111
- CoroTurn® TR
- CoroCut®

Inserts - PCD

- CoroTurn® 107
- CoroTurn® 111
- CoroCut®

Tools

- CoroTurn® 300
- CoroTurn® TR
- CoroCut® 1-2
- CoroCut® QD
- CoroCut® 3
- T-Max® Q-Cut

Adaptors

- Coromant Capto®

Engineered solutions

When standard or Tailor Made solutions do not fulfill your needs you can depend on Sandvik Coromant's wide experience in engineered tool solutions to handle particularly demanding criteria. Access our Tailor Made forms at www.sandvik.coromant.com

Safety information

Safety information in connection with grinding of cemented carbide

Material composition

Tool holders

Tool holders mainly contain iron (FE), and low alloy elements such as chromium, nickel, manganese, molybdenum and silicon.

Indexable inserts/cutting tools/round tools

Substances in cemented carbide products contain mostly wolfram carbide and cobalt. They may also contain carbides and carbonitrides of the following elements: titanium, tantalum, niobium, chromium, molybdenum and vanadium.

Routes of exposure

Grinding or heating of hard metal blanks or hard metal products will produce products that give off dangerous dust and fumes. Avoiding ingestion and contact with skin or eyes is very important.

Acute toxicity

Intake of the aforementioned substances is toxic. Inhalation may cause irritation and inflammation of the airways. Significantly higher acute inhalation toxicity has been reported during simultaneous inhalation of cobalt and tungsten carbide compared to inhalation of cobalt alone.

Skin contact can cause irritation and rash. Sensitive individuals may even experience an allergic reaction.

Chronic toxicity

Repeated inhalation of aerosols containing cobalt may cause obstruction of the airways. Prolonged exposure to increased concentrations may cause lung fibrosis or lung cancer. Epidemiological studies indicate that workers previously exposed to high concentrations of tungsten carbide/cobalt carried an increased risk of developing lung cancer.

Cobalt and nickel are potent skin sensitizers. Repeated or prolonged contact can cause irritation and sensitization.

Risk phrases

Toxic: danger of serious damage to health by prolonged exposure through inhalation

Toxic when inhaled

Limited evidence of a carcinogenic effect.

May cause sensitization by inhalation and skin contact

Preventive measures

Avoid formation and inhalation of dust. Use adequate local exhaust ventilation to keep personal exposure well below nationally authorised limits.

If ventilation is not available or adequate, use respirators appropriately approved for the purpose.

Use safety goggles or glasses with side shields when necessary.

Avoid repeated skin contact. Wear suitable gloves. Wash skin thoroughly after handling.

Use suitable protective clothing. Launder clothing if needed.

Do not eat, drink or smoke in the working area. Wash skin thoroughly before eating, drinking or smoking.



For the sake of the environment

Get into the Sandvik Coromant Recycling Concept (CRC) now!

The Sandvik Coromant Recycling Concept (CRC) is a comprehensive service for used carbide inserts and solid carbide tools offered by Sandvik Coromant to all its customers.

In the light of increasing consumption of non-renewable raw materials, the economic management of dwindling resources is a duty owed by all manufacturers.

Sandvik Coromant is playing its part by offering to collect used carbide inserts and solid carbide tools and recycle them in the most environmentally friendly way.

All used carbide inserts are collected in the collection box at the workplace.

When the collection box is sufficiently full, its contents are transferred to the transport box.

The full transport box is then sent to the nearest Sandvik Coromant office or to your Sandvik Coromant dealer who can also give you more information.

The benefits of the CRC speak for themselves

- A worldwide ISO and OHAS certified recycling system.
- Open to all Sandvik Coromant customers.
- Simple procedure with collection and transport boxes.
- Less waste, easing the burden on the environment.
- Better utilisation of resources.
- Other manufacturers' carbide inserts are also accepted.



Order collection boxes for each lathe, milling machine, drill or for your machining centre. We recommend one collection box for inserts and one separate box for solid carbide tools for each cutting workplace.

For detailed instructions on how to sell your used cemented carbide, please visit www.sandvik.coromant.com and select your market.

Collection box:	Order numbers
Transport box for solid carbide tools (plywood):	91617
Transport box inserts (plywood):	92994
	92995

Code key

Metric

C	N	G	A	12	04	08	T	010	20	R	A	WG
1	2	3	4	5	6	7	8	9	10	11	12	13

Inch

C	N	G	A	4	3	2	T	03	20	R	A	WG
1	2	3	4	5	6	7	8	9	10	11	12	13

1 Insert shape

C	D
K	R
S	T
V	W

2 Insert clearance angle

B	C
E	N
P	O Specific description

4 Insert type

A	Q
G	R
M	T
N	W
P	X
	Special design

3 Tolerances, metric

Class	S	IC / W1	
G	±0.13	±0.025	
M	±0.13	±0.05 – ±0.15 ¹⁾	
U	±0.13	±0.08 – ±0.25 ¹⁾	
E	±0.025	±0.025	

¹⁾Varies depending on the size of IC. See below.

Inscribed circle IC mm	Tolerance class	
	M	U
3.97		
5.0		
5.56		
6.0	±0.05	±0.08
6.35		
8.0		
9.525		
10.0		
12.0	±0.08	±0.13
12.7		
15.875	±0.10	±0.18
16.0		
19.05		
20.0		
25.0		
25.4	±0.13	±0.25
31.75		
32.0		
	±0.15	±0.25

For positive inserts iC is valid for a sharp corner. See cutting edge condition F. (Picture 8).

3 Tolerances, inch

Class	B:	A:	T:
A	±.0002	±.001	±.001
B	.0002	.001	.005
C	.0005	.001	.001
D	.0005	.001	.005
E	.001	.001	.001
F	.0002	.0005	.001
G	.001	.001	.005
H	.0005	.0005	.001
J	.0002	.002-.005	.001
K	.0005	.002-.005	.001
L	.001	.002-.005	.001
M	.002-.005	.002-.005	.005
U	.005-.012	.005-.010	.005
N	.002-.010	.002-.004	.001



A: Theoretical diameter of the insert inscribed circle.
T: Thickness of the insert.
B: See figures.








5 Insert size

Inscribed circle, inch		Cutting edge length, metric							
IC mm	IC inch	C	D	R	S	T	V	W	K
3.18	1/8"					05			
3.97	5/32"					06			
5.0				05 09					
6.0			06			11	11		
6.35	1/4"	06	07						
8.0				08					
9.525	3/8"	09	11	09	09	16	16	06	16 ¹⁾
10.0				10					
12.0				12					
12.7	1/2"	12	15	12	12	22	22	08	
15.875	5/8"	16		15	15	27			
16.0				16					
19.0	3/4"	19		19	19	33			
20.0				20					
25.0				25 ¹⁾					
25.4	1"			25 ²⁾	25				
31.75	1 1/4"	25		31					
32				32					

For rectangular and rhombic inserts cutting edge length is indicated in mm.

¹⁾ For insert shape K (KNMX, KNUX) only the theoretical cutting edge length is indicated.
¹⁾ Metric base design
²⁾ Inch base design

6 Insert thickness, S mm, inch				7 Nose radius, RE mm, inch		
						
Metric		Inch		Metric:	Inch:	Actual dimension:
01	S = 1.59	1.	S = .0625	00 = 0	00	Round
T1	S = 1.98	(1.2)	S = .075	01 = 0.1	03	.004
02	S = 2.38	(1.5)	S = 3/32	02 = 0.2	0	.008
03	S = 3.18	2	S = 1/8	04 = 0.4	1 = 1/64	.0156
T3	S = 3.97	(2.5)	S = 5/32	05 = 0.5		
04	S = 4.76	3	S = 3/16	08 = 0.8	2 = 1/32	.0312
05	S = 5.56	4	S = 1/4	10 = 1.0		
06	S = 6.35	5	S = 5/16	12 = 1.2	3 = 3/64	.047
07	S = 7.94	6	S = 3/8	15 = 1.5		
09	S = 9.52	6.3	S = .394	16 = 1.6	4 = 1/16	.0625
10	S = 10.00	7.6	S = .475	24 = 2.4	6 = 3/32	.094
12	S = 12.00			32 = 3.2	8 = 1/8	.125
Note: See example for approximation of metric nose radius. 16=1.6mm=.063≈.0625 inch						

8 Cutting edge condition			12 Insert Type (CBN)		
F		Sharp cutting edge	To allow a variety of machining demands to be met, several types of inserts comprising CBN and PCD is manufactured. To easy identify the different types Sandvik Coromant uses a letter to denote the variants.		
E (A)		ER treated cutting edge A (inch) E (metric)			
T		Negative land			
K		Double negative lands			
S		Negative land and ER treated cutting edge			
9 Chamfer width			A CBN, Multi Corner Inserts - Fully indexable - CBN brazed tip from top to bottom of the carbide carrier corners (double sided)		
	ISO mm	ANSI inch	B, H CBN, Multi Corner Inserts - Fully indexable - CBN brazed tip on the top and on the bottom of the carbide carrier corners (double sided).		
	010 BN = 0.10	03 BN = (.003)	E CBN, Single tip inserts - Non-indexable - CBN brazed to the top of one of the carbide carrier corners		
	015 BN = 0.15	06 BN = (.006)	F CBN, Multi tip inserts - Indexable - CBN brazed tip to the top of the carbide carrier corners (single sided)		
	020 BN = 0.20	08 BN = (.0078)	D CBN, Full top inserts - Indexable - CBN sintered to the complete top surface of the carbide carrier		
	025 BN = 0.25	08 BN = (.0098)	M CBN, Solid inserts - Fully indexable - Complete insert mode from CBN		
	070 BN = 0.70	30 BN = (.030)			
	150 BN = 1.50	60 BN = (.060)			
	200 BN = 2.00	80 BN = (.080)			
10 Chamfer angle, degrees			13 Geometry		
	15 GB = 15°	30 GB = 30°	Our unique Wiper and Xcel technologies can be used to boost productivity and generate superior surface finish.		
	20 GB = 20°	35 GB = 35°			
	25 GB = 25°				
11 Hand of insert			WG Wiper geometry for general purpose machining Allows high feed rates in HPT Suitable for finish machining of GCI		
Inserts designed solely for machining in left or right direction are indicated as below.			WH Wiper geometry optimized for HPT Low cutting forces for superior surface finish Designed for peak performance at HPT finishing feed rates		
R	Right hand design		Xcel XA / XA - for higher feed rates than WH and WG XB / XB - for higher feed rates than XA or for tightest surface finish tolerances with lower feed rates		
L	Left hand design		HGR Rough chip breaker for removal of case or induction hardened layer (skin)		

CoroTurn® XS

Insert for turning

CXS	04	T	098	A	10	-	22	06	R
1	2	3	4	13	5		9	10	12


Insert for grooving

CXS	06	F	100	-	62	15	A	R
1	2	3	6		9	10	11	12





Insert for threading

CXS	04	TH	050	VM	-	42	15	R
1	2	3	7	8		9	10	12

B

<p>1 Main code</p> <p>CXS = CoroTurn® XS</p>	<p>2 Insert size mm</p>  <p>04 = 4 mm (.157 inch) 05 = 5 mm (.197 inch) 06 = 6 mm (.236 inch) 07 = 7 mm (.276 inch)</p>	<p>3 Type of operation</p> <p>T = Turning TE = Turning copying, extended f_1-dimension F = Face grooving G = Grooving GX = Pre-parting R = Profiling full radius TH = Threading B = Back boring</p>
<p>4 Entering angle (Turning)</p> <p>E.g.: 098 = Entering angle 98° 98° Lead angle -8°</p>		

C

<p>5 Nose radius, RE mm (Turning)</p>  <p>E.g.: 10 = 0.1 mm (.004 inch) 15 = 0.15 mm (.006 inch) 20 = 0.2 mm (.008 inch)</p>	<p>6 Insert width, CW mm (Grooving)</p>  <p>E.g.: 100 = 1.00 mm</p>	<p>7 Pitch, mm (Threading)</p> <p>mm: pitch x 100 inch: No. of threads per inch x 10</p>
<p>8 Thread profile (Threading)</p> <p>VM = V-Profile 60° WH = Whitworth 55° NT = NPT 60° UN = UN 60° MM = MM 60° TR = Trapezoidal 30°</p>	<p>9 Min bore diameter, DMIN.</p>  <p>min. hole E.g.: 22 = 2.2 mm (.087 inch)</p>	<p>10 Penetration depth, LU</p>  <p>E.g.: 06 = 6 mm (.236 inch)</p>

D

<p>11 Type of curve (Face grooving)</p> <p>A = A-curved</p>	<p>13 Geometry</p> <p>- = Without chip forming geometry A = Chip forming geometry</p>
<p>12 Hand of insert</p> <p>R = Right hand style L = Left hand style</p>	

CoroTurn® XS

Boring bars

CXS	A	10	-	04
1	2	3		4

Double ended boring bars






CXS	A	10	-	04	-	04
1	2	3		4		5

Shank tool

CXS	-	1010	-	04	F	N
1		6		4	10	7

Coromant Capto® holder

C4	-	CXS	-	47	-	04
8		1		9		4

<p>1 Main code</p> <p>CXS = CoroTurn® XS</p>	<p>2 Type of bar</p> <p>A = Steel bar with internal coolant supply</p>	<p>3 Bar diameter, DCON</p>  <p>Metric 10 = 10 mm Inch 0500 = 1/2"</p>
<p>4 Insert size</p>  <p>04 = 4 mm (.157 inch) 05 = 5 mm (.197 inch) 06 = 6 mm (.236 inch) 07 = 7 mm (.276 inch)</p>	<p>5 Insert size for sub-spindle</p> <p>For double ended boring bars, same as 4.</p>	<p>6 Shank size (width and height), mm</p>  <p>H = 10 mm (.394 inch) B = 10 mm (.394 inch)</p>
<p>7 Hand of tool</p> <p>L = Left hand style R = Right hand style N = Neutral</p>	<p>9 Coromant Capto® length</p> <p>LF = 47 mm (1.850 inch)</p> 	<p>10 Shank style</p> <p>F = 0°</p> 
<p>8 Coromant Capto® size</p> <p>C3: DCON = 32 mm (1.260 inch) C4: DCON = 40 mm (1.575 inch) C5: DCON = 50 mm (1.968 inch) C6: DCON = 63 mm (2.480 inch)</p>		

CoroCut® MB

Insert for turning/back boring

MB	-	07	T	093	A	-	02	-	10	R
1		2	3	4	16		5		9	12

Insert for grooving/pre-parting

MB	-	07	G	070	-	00	-	10	R
1		2	3	6		5		9	12


Insert for threading



MB	-	07	TH	050	VM	-	10	R
1		2	3	7	8		9	12

Boring bars



MB	-	A	16	-	16	-	07	R
1		13	14		10		2	15


B

1 Main code MB = CoroCut® MB	2 Insert size, mm  07 = 7 mm (.276 inch) 09 = 9 mm (.354 inch)	3 Type of operation B = Back boring G = Grooving GX = Pre-parting R = Profiling full radius T = Turning TE = Turning copying, extended f_1 -dimension TH = Threading FA = Face grooving A-curve FB = Face grooving B-curve
4 Entering angle (Turning) E.g.: 093 = 93°		

5 Nose radius, RE mm (Turning)  E.g.: 00 = Sharp 02 = 0.2 mm (.008 inch)	6 Insert width, CW mm (Grooving)  E.g.: 100 = 1.00 mm (.039 inch)	7 Pitch (Threading) mm: pitch x 100 inch: No. of threads per inch x 10 (TPI)
---	---	---

C

8 Thread profile (Threading) VM = V profile 60° MM = Metric 60° WH = Whitworth 55° UN = UN 60° NT = NPT 60° AC = ACME 29° SA = STUB-ACME	9 Min bore diameter, DMIN (Insert)  E.g.: 10 = 10 mm (.394 inch)	10 Penetration depth, CW (boring bar)  Inch E.g.: 06 = 0.630 inch 08 = 0.787 inch 12 = 1.260 inch Metric E.g.: 16 = 16 mm
--	--	--




12 Hand of insert R = Right hand style L = Left hand style	14 Bar dia, DCON inch 	15 Shank type R = Cylindrical No symbol = With flats
---	---	---

D

13 Type of bar A = Steel bar with internal coolant supply E = Carbide shank bar	Inch 0625 = .625 inch Metric 16 = 16 mm	16 Geometry - = Without chip forming geometry A = Chip forming geometry
--	--	--

CoroCut® 1-2



N	123	H	2	-	0400	-	00	04	-	TF
1	2	3	4		5		6	7		8


1 Hand of insert R  N  L 	2 Main code 123	3 Seat size CoroCut® 1-2 D G K E H L F J M R CoroCut® 3 T = Right hand cutting U = Left hand cutting To correspond with seat size on holder.
--	--------------------------------------	--

B

Insert seat interchangeability:					
Insert seat size	Size, mm	Holder	Insert seat size	Size, mm	Holder
D	1.5	D	H	4.0	H
E	2.0	E	J	5.0	J, H
F	2.5	F, E	K	6.0	K, J, H
G	3.0	G, F, E	L	8.0	L
			M	9.0	M
			R	15.0	R

C

4 Number of edges 1 or 2  3 	5 Insert width E.g.: 0400 = .157 inch (4 mm) 0400 = .157 inch (4 mm)	6 Front angle E.g.: 00 = 0° 05 = 5°
---	---	--

7 Corner radius E.g.: 04 = .016 inch (0.4 mm) 08 = .031 inch (0.8 mm) 	8 Geometry designation First digit: Type of operation A = Aluminium/profiling C = Cut off T = Turning G = Grooving R = Profiling B = Blank Second digit: E = ER treated cutting edge F = Low feed M = Medium feed R = High feed O = Optimized for special areas S = Sharp cutting edge G = Blank	
---	--	--

D

A

ENG

Code	Page	Code	Page	Code	Page
266R/LG	C3				
C					
CCGW	A6-A7				
CCGX	A8				
CNG	A31				
CNGA	A16				
CNGA090304S01030AWH	A15-A17				
CNGM	A15				
CNGN	A31				
CNGX	A18				
CNMA	A15				
CXS	A35, B9, C5				
D					
DCGW	A9				
DCMW	A9				
DCWG	A9				
DNGA	A19-A21				
DNGM	A19				
DNMA	A19				
L					
L123	B6				
M					
MB	B11-B12, C7				
N					
N123	B3-B7				
R					
R123	B6				
RNG	A32				
RNGA	A22				
RNGN	A32				
S					
SCGW	A10				
SNG	A33				
SNGA	A23-A24				
SNGN	A33				
SNMA	A23				
T					
TCGW	A11				
TCMW	A11				
TNGA	A25-A26				
TNMA	A25				
TPGW	A13				
TR-DC	A3				
TR-VB	A4				
V					
VBGW	A12				
VBMW	A12				
VNGA	A27				
W					
WNGA	A28-A29				

B**C****D**