

A

T-Max® P kop voor draaien


Kantelpentype

CoroTurn® HP - Precisie koelmiddeltoevoer

KAPR

95,0°


B



C



D



						Afmetingen, mm						
	CZC _{MS}	DMIN ₁	CNSC	Bestelnummer	DCON _{MS}	LF	WF	BAR	NM	KG	MIID	
	09	25	34,0	1	SL-PCLNR/L-25-09HP-G	25,0	28,0	19,0	80	1,7	0,08	CNMG 09 03 08
	12	32	40,0	1	SL-PCLNR/L-32-12HP	32,0	36,0	22,0	80	5,0	0,16	CNMG 12 04 08
		40	50,0	1	SL-PCLNR/L-40-12HP	40,0	35,0	27,0	80	5,0	0,21	CNMG 12 04 08
	16	40	56,0	1	SL-PCLNR/L-40-16HP	40,0	42,0	27,0	80	5,0	0,27	CNMG 16 06 08

-G geeft gewijzigde hoofdimensies aan

R = Rechts, L = Links

E

Reserve onderdelen						
Bestelnummer	Kantelpen	Schroef	Onderlegplaat	Pen voor onderlegplaat	Pasbus	Spuitmond
SL-PCLNR/L-25-09HP-G	174,3-845-1	174,3-829			5552 058-02	5691 026-13
SL-PCLNR/L-32-12HP	174,3-848M	174,3-858	171,31-850M	174,3-861	5638 031-01	5691 026-03
SL-PCLNR/L-40-12HP	174,3-841M	174,3-821	171,31-850M	174,3-861	5638 031-01	5691 026-03
SL-PCLNR/L-40-16HP	438,3-840	438,3-831	171,31-852	174,3-864	5638 031-01	5691 026-03

Ga voor de complete lijst van reserveonderdelen naar www.sandvik.coromant.com

F

G

H



A152



F2



H36



H5



H2