

## UNC - Machinetappen, standaard

HSS

**5205 / 5215** Machinetappen, HSSEco, rechte groeven + gun,  
Staal < 850N/mm<sup>2</sup>, koper, aluminium



**5216** Machinetappen, HSSEco, hélicoïdaal 35°,  
Staal < 850N/mm<sup>2</sup>, koper, aluminium



UNC	P gangen/"	l1 mm	d2 mm	vierkant a <sub>h12</sub> mm	5205	5216
					HSS-ECo	HSS-ECo
DIN 371						
nr. 5	40	56	3,5	2,7	S	F
nr. 6	32	56	4,0	3,0	S	F
nr. 8	32	63	4,5	3,4	S	F
nr. 10	24	70	6,0	4,9	S	F
nr. 12	24	80	6,0	4,9	S	F
1/4"	20	80	7,0	5,2	S	F
5/16"	18	90	8,0	6,2	S	F
3/8"	16	90	9,0	7,0	S	F

S = magazijnartikel - F = fabriekslevering op 24/48h

UNC	P gangen/"	l1 mm	d2 mm	vierkant a <sub>h12</sub> mm	5215	5216
					HSS-ECo	HSS-ECo
DIN 376						
7/16"	14	100	8,0	6,2	S	F
1/2"	13	110	9,0	7,0	S	F
9/16"	12	110	11,0	9,0	S	F
5/8"	11	110	12,0	9,0	S	F
3/4"	10	125	14,0	11,0	S	F
7/8"	9	140	18,0	14,5	S	F
1"	8	160	18,0	14,5	S	F
1-1/8"	7	180	22,0	18,0	S	F
1-1/4"	7	180	22,0	18,0	S	F
1-1/2"	6	200	32,0	24,0	S	F
1-3/4"	5	220	36,0	29,0	F	F
2"	4,5	250	40,0	32,0	F	F

S = magazijnartikel - F = fabriekslevering op 24/48h

## UNC - Machinetappen, staal & roestvrijstaal

PM

**T200-XM100DE/C145** Machinetappen, HSSE-PM, rechte groeven + gun  
Staal <1100N/mm<sup>2</sup>, RVS <850 N/mm<sup>2</sup>, gietijzer  
Stoomontlaten (zwarte) uitvoering



**T300-XM100DE/C145** Machinetappen, HSSE-PM, hélicoïdaal 45°  
Staal <1100N/mm<sup>2</sup>, RVS <850 N/mm<sup>2</sup>  
Stoomontlaten (zwarte) uitvoering



UNC	P gangen/"	l1 mm	d2 mm	vierkant a <sub>h12</sub> mm	T200-XM100DE	T300-XM100DE
					C145 HSSE-PM PVD Fe-coating	C145 HSSE-PM PVD Fe-coating
DIN 2184-1						
nr. 4	40	56	3,5	2,7	F	F
nr. 5	40	56	3,5	2,7	F	F
nr. 6	32	56	4,0	3,0	F	F
nr. 8	32	63	4,5	3,4	F	F
nr. 10	24	70	6,0	4,9	F	F
nr. 12	24	80	6,0	4,9	F	F
1/4"	20	80	7,0	5,2	F	F
5/16"	18	90	8,0	6,2	F	F
3/8"	16	90	9,0	7,0	F	F
7/16"	14	100	8,0	6,2	F	F
1/2"	13	110	9,0	7,0	F	F
9/16"	12	110	11,0	9,0	F	F
5/8"	11	110	12,0	9,0	F	F
3/4"	10	125	14,0	11,0	F	F
7/8"	9	140	18,0	14,5	F	F
1"	8	160	18,0	14,5	F	F

S = magazijnartikel - F = fabriekslevering op 24/48h

