


K 37

Slagmoerdopsleutel
1.1/2"
6-kant




- > Uitvoering volgens DIN 3129, ISO 2725-2
- > Machinebediening
- > Binnenaandrijfvierkant volgens DIN 3121 - H 40, ISO 1174

* niet genormeerd

Code	Nr.	mm	L	d1	d2	t	Aanbevolen toebehoren	kg
6328130	K 37 46	46	95,0	76,0	86,0	27,0	KB 3770, KB 3775	2,265
6328210*	K 37 50	50	95,0	81,0	86,0	29,0	KB 3770, KB 3775	2,306
6328480	K 37 55	55	95,0	86,0	86,0	35,0	KB 3770, KB 3775	2,459
6328560	K 37 60	60	95,0	93,0	86,0	38,0	KB 3770, KB 3775	2,744
6328640	K 37 65	65	97,0	97,0	86,0	40,0	KB 3770, KB 3775	3,215
6328720	K 37 70	70	102,0	105,0	86,0	43,0	KB 3770, KB 3775	3,535
6328800	K 37 75	75	107,0	110,0	86,0	45,0	KB 3770, KB 3775	3,735
6328990	K 37 80	80	110,0	116,0	86,0	50,0	KB 3770, KB 3775	4,185
6329020	K 37 85	85	110,0	125,0	86,0	55,0	KB 3770, KB 3775	4,795
6329100	K 37 90	90	110,0	130,0	86,0	55,0	KB 3770, KB 3775	5,460
6329290*	K 37 95	95	110,0	137,0	86,0	55,0	KB 6470, KB 6475	9,000
6329370*	K 37 100	100	110,0	140,0	127,0	55,0	KB 6470, KB 6475	8,095
6329450*	K 37 105	105	120,0	148,0	127,0	58,0	KB 6470, KB 6475	7,240
6329530*	K 37 110	110	120,0	154,0	127,0	58,0	KB 6470, KB 6475	9,380
6329610*	K 37 115	115	120,0	160,0	127,0	60,0	KB 6470, KB 6475	10,575
6329880*	K 37 120	120	120,0	167,0	127,0	60,0	KB 6470, KB 6475	11,770

K 37 L

Slagmoerdopsleutel
1.1/2"
6-kant, lange uitvoering



- > Machinebediening
- > Binnenaandrijfvierkant volgens DIN 3121 - H 40, ISO 1174

Code	Nr.	mm	L	d1	d2	t	Aanbevolen toebehoren	kg
6330110	K 37L 41	41	140,0	70,0	86,0	22,0	KB 3770, KB 3775	4,400
6330380	K 37L 46	46	140,0	75,0	86,0	25,5	KB 3770, KB 3775	4,330
6330460	K 37L 50	50	140,0	80,0	86,0	27,0	KB 3770, KB 3775	4,365
6330540	K 37L 55	55	140,0	86,0	86,0	30,0	KB 3770, KB 3775	3,950
6330620	K 37L 60	60	140,0	92,0	86,0	33,0	KB 3770, KB 3775	4,135
6330700	K 37L 65	65	140,0	100,0	86,0	35,0	KB 3770, KB 3775	4,620
6330890	K 37L 70	70	140,0	105,0	86,0	38,0	KB 3770, KB 3775	4,805
6330970	K 37L 75	75	140,0	109,0	86,0	41,0	KB 3770, KB 3775	5,395
6331000	K 37L 80	80	140,0	115,0	86,0	44,0	KB 3770, KB 3775	8,220
6331190	K 37L 85	85	140,0	121,0	86,0	47,0	KB 3770, KB 3775	6,154
6331270	K 37L 90	90	140,0	130,0	86,0	49,0	KB 3770, KB 3775	6,595
6331350	K 37L 95	95	150,0	137,0	127,0	49,0	KB 6470, KB 6475	9,960
6331430	K 37L 100	100	150,0	144,0	127,0	54,0	KB 6470, KB 6475	9,964
6331510	K 37L 105	105	150,0	154,0	127,0	54,0	KB 6470, KB 6475	12,500
6331780	K 37L 110	110	160,0	157,0	127,0	62,0	KB 6470, KB 6475	12,800
6331860	K 37L 115	115	160,0	164,0	127,0	67,0	KB 6470, KB 6475	12,225
6331940	K 37L 120	120	170,0	167,0	127,0	67,0	KB 6470, KB 6475	13,845

KB 3721

Verloopstuk
1.1/2" - 1"
tbv slagmoerdopsleutels



- > Met aandrijfvierkant volgens DIN 3121, ISO 1174, vorm F en H

Code	Nr.	"	mm	"	mm	mm	kg
6676410	KB 3721	1.1/2"	40,0	1"	25	95	1,992

KB 3764

Slag-verloopstuk
1.1/2" - 2.1/2"
tbv slagmoerdopsleutels

> Met aandrijfvierkant
volgens DIN 3121,
ISO 1174, vorm F en H



Code	Nr.	□"	□mm	■"	■mm	↳mm↳	
1531220	KB 3764	1.1/2"	40,0	2.1/2"	63	93	3,6

KB 3770

Borgring tbv
slagmoerdopsleutels
1.1/2"



Code	Nr.	Omschrijving	∅	
6676760	KB 3770	Borgring ∅ 75 mm	75,0	0,026

KB 3775

Borgstift tbv
slagmoerdopsleutels
1.1/2"




Code	Nr.	Omschrijving	∅	↳mm↳	
6676840	KB 3775	Borgstift ∅ 6 mm	6,0	75	0,017

K 64

Slagmoerdopsleutel
2.1/2"
6-kant

> Uitvoering volgens
DIN 3129, ISO 2725-2
> Machinebediening
> Binnenaandrijfvierkant
volgens DIN 3121 - H 63,
ISO 1174



Code	Nr.	∅mm	L	d1	d2	t	Aanbevolen toebehoren	
6371300	K 64 75	75	140,0	110,0	127,0	46,0	KB 6470, KB 6475	7,350
6371490	K 64 80	80	140,0	116,0	127,0	50,0	KB 6470, KB 6475	7,015
6371570	K 64 85	85	140,0	124,0	127,0	50,0	KB 6470, KB 6475	7,295
6371650	K 64 90	90	145,0	130,0	127,0	55,0	KB 6470, KB 6475	7,955
6371730	K 64 95	95	145,0	136,0	127,0	55,0	KB 6470, KB 6475	8,120
6371810	K 64 100	100	150,0	140,0	127,0	58,0	KB 6470, KB 6475	8,905
6372030	K 64 105	105	155,0	148,0	127,0	58,0	KB 6470, KB 6475	9,145
6372110	K 64 110	110	160,0	154,0	127,0	64,0	KB 6470, KB 6475	11,000
6372380	K 64 115	115	165,0	160,0	127,0	67,0	KB 6470, KB 6475	11,130
6372460	K 64 120	120	170,0	167,0	127,0	70,0	KB 6470, KB 6475	12,030

KB 6437

Verloopstuk
2.1/2" - 1.1/2"
tbv slagmoerdopsleutels

> Met aandrijfvierkant
volgens DIN 3121,
ISO 1174, vorm F en H



Code	Nr.	□"	□mm	■"	■mm	↳mm↳	
6699700	KB 6437	2.1/2"	63,0	1.1/2"	40	138	7,09