


CoroCut® 2 cutting unit for parting and grooving

Screw clamp design

Precision coolant supply



SSC	CZC _{MS}	CDX	CNSC	Ordering code	Dimensions, mm, inch						MIID
					DCON _{MS}	LF	WF	OAH	NM	KG	
E	C3	8.0	3	C2R-CC3-R/LE08CB	32	50.0	22.0	41.0	4.0	0.30	C21-E2N-0200-
		.315			1.260	1.969	.866	1.614			
	C3	15.0	3	C2R-CC3-R/LE15CB	32	55.0	22.0	41.0	4.5	0.28	C21-E2N-0200-
		.591			1.260	2.165	.866	1.614			
	C4	8.0	3	C2R-CC4-R/LE08CB	40	55.0	27.0	45.0	4.0	0.47	C21-E2N-0200-
		.315			1.575	2.165	1.063	1.771			
C4	15.0	3	C2R-CC4-R/LE15CB	40	60.0	27.0	45.0	4.5	0.45	C21-E2N-0200-	
	.591			1.575	2.362	1.063	1.771				
C5	8.0	3	C2R-CC5-R/LE08CB	50	55.0	35.0	57.0	4.0	0.74	C21-E2N-0200-	
	.315			1.969	2.165	1.378	2.244				
C5	15.0	3	C2R-CC5-R/LE15CB	50	60.0	35.0	57.0	4.5	0.71	C21-E2N-0200-	
	.591			1.969	2.362	1.378	2.244				
F	C3	10.0	3	C2R-CC3-R/LF10CB	32	50.0	22.0	41.0	4.0	0.28	C21-F2N-0250-
		.394			1.260	1.969	.866	1.614			
	C3	15.0	3	C2R-CC3-R/LF15CB	32	55.0	22.0	41.0	4.5	0.28	C21-F2N-0250-
		.591			1.260	2.165	.866	1.614			
	C4	10.0	3	C2R-CC4-R/LF10CB	40	55.0	27.0	45.0	4.0	0.45	C21-F2N-0250-
		.394			1.575	2.165	1.063	1.771			
C4	15.0	3	C2R-CC4-R/LF15CB	40	60.0	27.0	45.0	4.5	0.45	C21-F2N-0250-	
	.591			1.575	2.362	1.063	1.771				
C5	10.0	3	C2R-CC5-R/LF10CB	50	55.0	35.0	57.0	4.0	0.71	C21-F2N-0250-	
	.394			1.969	2.165	1.378	2.244				
C5	20.0	3	C2R-CC5-R/LF20CB	50	65.0	35.0	57.0	4.5	0.70	C21-F2N-0250-	
	.787			1.969	2.559	1.378	2.244				
G	C3	10.0	3	C2R-CC3-R/LG10CB	32	50.0	22.0	41.0	4.0	0.28	C21-G2N-0300-
		.394			1.260	1.969	.866	1.614			
	C3	15.0	3	C2R-CC3-R/LG15CB	32	55.0	22.0	41.0	4.5	0.28	C21-G2N-0300-
		.591			1.260	2.165	.866	1.614			
	C3	20.0	3	C2R-CC3-R/LG20CB	32	60.0	22.0	41.0	4.5	0.27	C21-G2N-0300-
		.787			1.260	2.362	.866	1.614			
C4	10.0	3	C2R-CC4-R/LG10CB	40	55.0	27.0	45.0	4.0	0.44	C21-G2N-0300-	
	.394			1.575	2.165	1.063	1.771				
C4	15.0	3	C2R-CC4-R/LG15CB	40	60.0	27.0	45.0	4.5	0.45	C21-G2N-0300-	
	.591			1.575	2.362	1.063	1.771				
C4	20.0	3	C2R-CC4-R/LG20CB	40	65.0	27.0	45.0	4.5	0.49	C21-G2N-0300-	
	.787			1.575	2.559	1.063	1.771				
C5	10.0	3	C2R-CC5-R/LG10CB	50	55.0	35.0	57.0	4.0	0.70	C21-G2N-0300-	
	.394			1.969	2.165	1.378	2.244				
C5	15.0	3	C2R-CC5-R/LG15CB	50	60.0	35.0	57.0	4.5	0.71	C21-G2N-0300-	
	.591			1.969	2.362	1.378	2.244				
C5	20.0	3	C2R-CC5-R/LG20CB	50	65.0	35.0	57.0	4.5	0.69	C21-G2N-0300-	
	.787			1.969	2.559	1.378	2.244				
C6	10.0	3	C2R-CC6-R/LG10CB	63	60.0	45.0	64.5	4.0	1.18	C21-G2N-0300-	
	.394			2.480	2.362	1.772	2.539				
C6	15.0	3	C2R-CC6-R/LG15CB	63	65.0	45.0	64.5	4.5	1.18	C21-G2N-0300-	
	.591			2.480	2.559	1.772	2.539				
C6	20.0	3	C2R-CC6-R/LG20CB	63	70.0	45.0	64.5	4.5	1.34	C21-G2N-0300-	
	.787			2.480	2.756	1.772	2.539				