



T-Max® P snijgereedschap voor draaien

Rigid clamp-ontwerp


Coromant Capto® - inwendige koelmiddeltoevoer



KAPR



95.0°



- CNMM
- CNMG
- CNMA, CNGA

	CZC _{MS}	DMIN ₁	DMIN ₂	CNSC	Bestelnummer	Afmetingen, mm						MIID		
						DCON _{MS}	LF	WF	BAR	NM	KG			
	09	C4	60,0	140,0	3	C4-DCLNR/L-27050-09	40,0	50,0	27,0	10	1,7	0,41	CNMG 09 03 08	
	12	C3	60,0	121,0	3	C3-DCLNR/L-22045-12	32,0	45,0	22,0	10	3,9	0,26	CNMG 12 04 08	
		C4	110,0	140,0	3	C4-DCLNR/L-27050-12	40,0	50,0	27,0	10	3,9	0,44	CNMG 12 04 08	
		C5	110,0	165,0	3	C5-DCLNR/L-35060-12	50,0	60,0	35,0	10	3,9	0,79	CNMG 12 04 08	
		C6	110,0	190,0	3	C6-DCLNR/L-45065-12	63,0	65,0	45,0	10	3,9	1,33	CNMG 12 04 08	
		C8	110,0	250,0	3	C8-DCLNR/L-55080-12	80,0	80,0	55,0	10	3,9	2,56	CNMG 12 04 08	
		16	C4	125,0	145,0	3	C4-DCLNR/L-27055-16	40,0	55,0	27,0	10	6,4	0,48	CNMG 16 06 12
			C5	125,0	165,0	3	C5-DCLNR/L-35060-16	50,0	60,0	35,0	10	6,4	0,79	CNMG 16 06 12
		C6	125,0	190,0	3	C6-DCLNR/L-45065-16	63,0	65,0	45,0	10	6,4	1,43	CNMG 16 06 12	
		C8	125,0	250,0	3	C8-DCLNR/L-55080-16	80,0	80,0	55,0	10	6,4	2,59	CNMG 16 06 12	
		19	C5	80,0	165,0	3	C5-DCLNR/L-35060-19	50,0	60,0	35,0	10	6,4	0,87	CNMG 19 06 12
			C6	81,0	190,0	3	C6-DCLNR/L-45065-19	63,0	65,0	45,0	10	6,4	1,34	CNMG 19 06 12
			C8	100,0	250,0	3	C8-DCLNR/L-55080-19	80,0	80,0	55,0	10	6,4	2,61	CNMG 19 06 12

R = Rechts, L = Links

Reserve onderdelen						
	CZC _{MS}	Onderlegplaat schroef	Onderlegplaat	Spankapset	Spuitmond	
	09	C4	5513 020-04	5322 236-04	5412 028-011	5691 045-01
	12	C3	5513 020-02	5322 236-03	5412 028-021	
	12	C4-C8	5513 020-02	5322 234-01	5412 028-021	5691 045-01
	16	C4-C8	5513 020-07	5322 234-03	5412 028-031	5691 045-01
	19	C5-C8	5513 020-07	5322 236-01	5412 028-041	5691 045-01

Ga voor de complete lijst van reserveonderdelen naar www.sandvik.coromant.com



A152



F2



E1



G1



H36



H10



H5

