

T-Max® P snijgereedschap voor draaien


Rigid clamp-ontwerp

Coromant Capto® - inwendige koelmiddeltoevoer




- WNMM,
- WNMG
- WNGA, WNMA

KAPR



95.0°



| CZC _{MS} | DMIN ₁ | DMIN ₂ | CNSC | Bestelnummer | Afmetingen, mm | | | | | | MIID | |
|-------------------|-------------------|-------------------|-------|--------------|--------------------|------|------|------|----|-----|------|---------------|
| | | | | | DCON _{MS} | LF | WF | BAR | NM | KG | | |
| 06 | C3 | 60,0 | 116,0 | 3 | C3-DWLNRL-22040-06 | 32,0 | 40,0 | 22,0 | 10 | 1,7 | 0,21 | WNMG 06 04 08 |
| | C4 | 60,0 | 140,0 | 3 | C4-DWLNRL-27050-06 | 40,0 | 50,0 | 27,0 | 10 | 1,7 | 0,43 | WNMG 06 04 08 |
| | C5 | 65,0 | 165,0 | 3 | C5-DWLNRL-35060-06 | 50,0 | 60,0 | 35,0 | 10 | 1,7 | 0,74 | WNMG 06 04 08 |
| 08 | C6 | 81,0 | 190,0 | 3 | C6-DWLNRL-45065-06 | 63,0 | 65,0 | 45,0 | 10 | 1,7 | 1,33 | WNMG 06 04 08 |
| | C4 | 110,0 | 140,0 | 3 | C4-DWLNRL-27050-08 | 40,0 | 50,0 | 27,0 | 10 | 3,9 | 0,43 | WNMG 08 04 08 |
| | C5 | 110,0 | 165,0 | 3 | C5-DWLNRL-35060-08 | 50,0 | 60,0 | 35,0 | 10 | 3,9 | 0,74 | WNMG 08 04 08 |
| 08 | C6 | 110,0 | 190,0 | 3 | C6-DWLNRL-45065-08 | 63,0 | 65,0 | 45,0 | 10 | 3,9 | 1,34 | WNMG 08 04 08 |
| | C8 | 110,0 | 250,0 | 3 | C8-DWLNRL-55080-08 | 80,0 | 80,0 | 55,0 | 10 | 3,9 | 2,58 | WNMG 08 04 08 |

R = Rechts, L = Links

| Reserve onderdelen | | | | | |
|--------------------|-----------------------|---------------|-------------|--------------|--|
| CZC _{MS} | Onderlegplaat schroef | Onderlegplaat | Spankapset | Sputmond | |
| 06 | C3 | 5513 020-04 | 5322 328-01 | 5412 028-011 | |
| 06 | C4 | 5513 020-04 | 5322 328-01 | 5412 028-011 | |
| 06 | C5-C6 | 5513 020-04 | 5322 328-01 | 5412 028-011 | |
| 08 | C4 | 5513 020-02 | 5322 331-12 | 5412 028-021 | |
| 08 | C5-C8 | 5513 020-02 | 5322 331-12 | 5412 028-021 | |

Ga voor de complete lijst van reserveonderdelen naar www.sandvik.coromant.com

