

## M - HSSE - Moertappen

Artikelnr.: NFE66101

- Draairichting: rechts
- Spaangroeven: recht
- Boringen: doorlopend
- Gebruik: standaard tot 900N/mm<sup>2</sup> - 27 HRC



Artikelnr: **NFE66101**

| Ø   | P    | H     | L   | I1   | d2   | ☐ |
|-----|------|-------|-----|------|------|---|
| M3  | 0.5  | 2.5   | 280 | 12.5 | 2.3  |   |
| M4  | 0.7  | 3.3   | 280 | 18   | 2.9  |   |
| M5  | 0.8  | 4.2   | 280 | 20   | 3.8  |   |
| M6  | 1    | 5     | 280 | 25   | 4.5  |   |
| M7  | 1    | 6     | 280 | 25   | 5.5  |   |
| M8  | 1.25 | 6.75  | 280 | 32   | 6.1  |   |
| M10 | 1.5  | 8.5   | 280 | 38   | 7.7  |   |
| M12 | 1.75 | 10.25 | 420 | 44   | 9.3  |   |
| M14 | 2    | 12    | 420 | 50   | 10.9 |   |
| M16 | 2    | 14    | 520 | 50   | 12.9 |   |
| M18 | 2.5  | 15.5  | 520 | 63   | 14.1 |   |
| M20 | 2.5  | 17.5  | 520 | 63   | 16.1 |   |
| M22 | 2.5  | 19.5  | 520 | 63   | 18   |   |
| M24 | 3    | 21    | 520 | 75   | 19.3 |   |