

# T-Max® P boorbaar voor draaien


Kantelpentype

Cilindrisch met platte vlakken - Precisie koelmiddeltoevoer




- DNMM, DNMX
- DNMG
- DNMA, DNGA

KAPR



93.0°



								Afmetingen, mm											MIID
		CZC <sub>MS</sub>	DMIN <sub>1</sub>	RMPX	OHX	OHN	CNSC	Bestelnummer	DCON <sub>MS</sub>	H	BD	LF	WF	CNT					
	11	25	32.0	27°	100.0	37.7	1	A25T-PDUNR/L11HP	25.0	23.0	25.0	300.0	17.0	G 1/8-28	275	2.0	0.95	DNMG 11 04 08	
		32	40.0	27°	128.0	36.2	1	A32T-PDUNR/L11HP	32.0	30.0	32.0	300.0	22.0	G 1/8-28	275	2.0	1.68	DNMG 11 04 08	
		15	40	50.0	27°	160.0	40.6	1	A40T-PDUNR/L15HP	40.0	37.0	40.0	300.0	27.0	G 1/8-28	275	5.0	2.67	DNMG 15 06 08
			50	63.0	27°	200.0	40.6	1	A50U-PDUNR/L15HP	50.0	47.0	50.0	350.0	35.0	G 1/8-28	275	5.0	5.03	DNMG 15 06 08

R = Rechts, L = Links

Reserve onderdelen					
Bestelnummer	Kantelpen	Schroef	Onderlegplaat	Pen voor onderlegplaat	Spuitmond
A25T-PDUNR/L11HP	5432 015-021	438.3-830			5691 026-13
A32T-PDUNR/L11HP	5432 001-01	174.3-820M	5322 255-01	174.3-860	5691 026-13
A40T-PDUNR/L15HP	174.3-847M	174.3-830	171.35-851M	174.3-861	5691 026-13
A50U-PDUNR/L15HP	174.3-847M	174.3-830	171.35-851M	174.3-861	5691 026-13

Ga voor de complete lijst van reserveonderdelen naar [www.sandvik.coromant.com](http://www.sandvik.coromant.com)

