


12-UN - HSSG - Korte tap



Artikelnr.: 5309

- Draairichting: rechts
- Spaangroeven: recht (zonder schilaansnijding)
- Ingang: 2-3 spoed
- Type: Form C
- Boringen: doorlopend & blind
- Gebruik: standaard tot 900N/mm² - 27 HRC



Prototap

Artikelnr: **5309**

12-UN	D1	D2	L1	L2		
UN 1/2 x 12	12,70	9,0	75	25	7,0	10,65
UN 5/8 x 12	15,88	12,0	80	25	9,0	13,80
UN 11/16 x 12	17,46	14,0	80	25	11,0	15,40
UN 3/4 x 12	19,05	14,0	80	25	11,0	17,00
UN 13/16 x 12	20,64	16,0	80	25	12,0	18,60
UN 7/8 x 12	22,23	18,0	80	25	14,5	20,20
UN 15/16 x 12	23,81	18,0	90	25	14,5	21,80
UN 1.1/16 x 12	26,99	20,0	90	28	16,0	24,90
UN 1.3/16 x 12	30,16	22,0	90	28	18,0	28,10
UN 1.5/16 x 12	33,34	28,0	125	32	22,0	31,30
UN 1.7/16 x 12	36,51	28,0	125	32	22,0	34,50
UN 1.5/8 x 12	41,28	32,0	125	32	24,0	39,20
UN 1.3/4 x 12	44,45	36,0	125	32	29,0	42,40
UN 1.7/8 x 12	47,63	36,0	140	32	29,0	45,60
UN 2 x 12	50,80	40,0	140	32	32,0	48,75
UN 2.1/8 x 12	53,98	35,5	200	70	28,0	51,90
UN 2.1/4 x 12	57,15	40,0	221	76	31,5	55,10
UN 2.1/2 x 12	63,50	40,0	224	79	31,5	61,50
UN 2.3/4 x 12	69,85	45,0	234	79	35,5	67,80
UN 3" x 12	76,20	50,0	258	83	40,0	74,20
UN 3.1/4 x 12	82,55	50,0	261	86	40,0	80,50
UN 3.1/2 x 12	88,90	50,0	261	86	40,0	86,90
UN 3.3/4 x 12	95,25	56,0	279	89	45,0	93,20
UN 4" x 12	101,60	56,0	279	89	45,0	99,60