





# T-Max® P schachtgereedschap voor draaien


## Rigid clamp-ontwerp



KAPR

DDHNR/L  
107.5°DDJNR/L  
93.0°DDNNN  
62.5°

- DNMM, DNMX
- DNMG
- DNMA, DNGA



		Afmetingen, mm											
		CZC <sub>MS</sub>	RMPX	OHX	Bestelnummer	B	H	LF	WF	HF	NM	KG	MIID
	15	20 x 20	12°	36,1	DDHNR/L 2020K 15	20,0	20,0	125,0	25,0	20,0	3,9	0,42	DNMG 15 06 08
		25 x 25	12°	36,1	DDHNR/L 2525M 15	25,0	25,0	150,0	32,0	25,0	3,9	0,76	DNMG 15 06 08
		32 x 25	12°	36,1	DDHNR/L 3225P 15	25,0	32,0	170,0	32,0	32,0	3,9	1,09	DNMG 15 06 08
		32 x 32	12°	36,1	DDHNR/L 3232P 15	32,0	32,0	170,0	40,0	32,0	3,9	1,34	DNMG 15 06 08
	11	16 x 16	27°	30,1	DDJNR/L 1616H 11	16,0	16,0	100,0	20,0	16,0	1,7	0,22	DNMG 11 04 08
		20 x 20	27°	30,2	DDJNR/L 2020K 11	20,0	20,0	125,0	25,0	20,0	1,7	0,40	DNMG 11 04 08
		25 x 25	27°	30,2	DDJNR/L 2525M 11	25,0	25,0	150,0	32,0	25,0	1,7	0,73	DNMG 11 04 08
	15	20 x 20	27°	39,4	DDJNR/L 2020K 15	20,0	20,0	125,0	25,0	20,0	3,9	0,43	DNMG 15 06 08
		25 x 25	27°	39,4	DDJNR/L 2525M 15	25,0	25,0	150,0	32,0	25,0	3,9	0,75	DNMG 15 06 08
		32 x 25	27°	39,4	DDJNR/L 3225P 15	25,0	32,0	170,0	32,0	32,0	3,9	1,06	DNMG 15 06 08
		32 x 32	27°	39,4	DDJNR/L 3232P 15	32,0	32,0	170,0	40,0	32,0	3,9	1,33	DNMG 15 06 08
	11	20 x 20	57°	31,2	DDNNN 2020K 11	20,0	20,0	125,0	10,5	20,0	1,7	0,39	DNMG 11 04 08
		25 x 25	57°	31,2	DDNNN 2525M 11	25,0	25,0	150,0	13,0	25,0	1,7	0,72	DNMG 11 04 08
	15	25 x 25	57°	40,8	DDNNN 2525M 15	25,0	25,0	150,0	13,0	25,0	3,9	0,72	DNMG 15 06 08
		32 x 25	57°	40,8	DDNNN 3225P 15	25,0	32,0	170,0	13,0	32,0	3,9	1,03	DNMG 15 06 08
		32 x 32	57°	40,8	DDNNN 3232P 15	32,0	32,0	170,0	16,5	32,0	3,9	1,28	DNMG 15 06 08

N = Neutraal, R = Rechts, L = Links

Reserve onderdelen

Onderlegplaat schroef	Onderlegplaat	Spankasset
5513 020-04	5322 267-01	5412 028-011
5513 020-02	5322 266-02	5412 028-021

Ga voor de complete lijst van reserveonderdelen naar [www.sandvik.coromant.com](http://www.sandvik.coromant.com)

A152



F2



E1



H36



H10