

A  
B  
C  
D  
E  
F  
G  
H

ALGEMEEN DRAAIEN Uitwendige gereedschappen

# T-Max® P schachtgereedschap voor draaien

Rigid clamp-ontwerp

KAPR  
DSSNR/L  
45.0°

DSKNR/L  
75.0°

- SNMM
- SNMG
- SNMA, SNGA

Afmetingen, mm

CZC <sub>MS</sub>	RMPX	OHX	Bestelnummer	Afm. (mm)							NM		KG		MIID	
				B	H	LPR	LF	WF	HF							
12	25 x 25	10°	23.6	DSKNR/L 2525M 12	25,0	25,0	153,1	150,0	32,0	25,0	3,9	0,79			SNMG 12 04 08	
	32 x 25	10°	23,7	DSKNR/L 3225P 12	25,0	32,0	173,1	170,0	32,0	32,0	3,9	1,13			SNMG 12 04 08	
12	20 x 20	0°	27,5	DSSNR/L 2020K 12	20,0	20,0	133,3	125,0	25,0	20,0	3,9	0,33			SNMG 12 04 08	
	25 x 25	0°	27,5	DSSNR/L 2525M 12	25,0	25,0	158,3	150,0	32,0	25,0	3,9	0,80			SNMG 12 04 08	
	32 x 25	0°	27,4	DSSNR/L 3225P 12	25,0	32,0	178,3	170,0	32,0	32,0	3,9	1,13			SNMG 12 04 08	
	32 x 32	0°	27,4	DSSNR/L 3232P 12	32,0	32,0	178,3	170,0	40,0	32,0	3,9	1,40			SNMG 12 04 08	
	15	25 x 25	0°	32,0	DSSNR/L 2525M 15	25,0	25,0	160,2	150,0	32,0	25,0	6,4	0,90			SNMG 15 06 12
		32 x 25	0°	33,1	DSSNR/L 3225P 15	25,0	32,0	180,2	170,0	32,0	32,0	6,4	1,16			SNMG 15 06 12
19	32 x 32	0°	33,1	DSSNR/L 3232P 15	32,0	32,0	180,2	170,0	40,0	32,0	6,4	1,44			SNMG 15 06 12	
	32 x 32	0°	37,0	DSSNR/L 3232P 19	32,0	32,0	182,5	170,0	40,0	32,0	6,4	1,47			SNMG 19 06 12	

R = Rechts, L = Links

Reserve onderdelen

CZC <sub>MS</sub>	Onderlegplaat schroef	Onderlegplaat	Spankaset	
12	20 x 20-32 x 32	5513 020-02	5322 425-01	5412 028-021
15	25 x 25-32 x 32	5513 020-07	5322 425-03	5412 028-031
19	32 x 32	5513 020-07	5322 425-04	5412 028-041

Ga voor de complete lijst van reserveonderdelen naar [www.sandvik.coromant.com](http://www.sandvik.coromant.com)

A152 F2 E1 H36 H10

A 208