


T-Max® P schachtgereedschap voor draaien

Rigid clamp-ontwerp




- WNMM,
- WNMG
- WNGA, WNMA

KAPR



95.0°



	CZC _{MS}	OHX	Bestelnummer	Afmetingen, mm							NM	KG	MIID
				B	H	LF	WF	HF					
	06	16 x 16	26,4	DWLNRL 1616H 06	16,0	16,0	100,0	20,0	16,0	1,7	0,22	WNMG 06 04 08	
		20 x 20	27,1	DWLNRL 2020K 06	20,0	20,0	125,0	25,0	20,0	1,7	0,42	WNMG 06 04 08	
		25 x 25	27,1	DWLNRL 2525M 06	25,0	25,0	150,0	32,0	25,0	1,7	0,76	WNMG 06 04 08	
	08	20 x 20	34,3	DWLNRL 2020K 08	20,0	20,0	125,0	25,0	20,0	3,9	0,43	WNMG 08 04 08	
		25 x 25	34,3	DWLNRL 2525M 08	25,0	25,0	150,0	32,0	25,0	3,9	0,76	WNMG 08 04 08	
		32 x 25	35,0	DWLNRL 3225P 08	25,0	32,0	170,0	32,0	32,0	3,9	1,10	WNMG 08 04 08	
	32 x 32	34,3	DWLNRL 3232P 08	32,0	32,0	170,0	40,0	32,0	3,9	1,36	WNMG 08 04 08		

R = Rechts, L = Links

Reserve onderdelen				
	CZC _{MS}	Onderlegplaat schroef	Onderlegplaat	Spankapset
06	16 x 16-25 x 25	5513 020-04	5322 328-01	5412 028-011
08	20 x 20-32 x 32	5513 020-02	5322 331-12	5412 028-021

Ga voor de complete lijst van reserveonderdelen naar www.sandvik.coromant.com

